# AUSTRALIAN BUILDERS™ HOME HANDYPAC™ QUICK-SET MORTAR





Australian Builders Home Handypac Quick Set Mortar Mix is a versatile "Dry Mix" just add water ready to use sand, cement & lime mix, ideal for all the little fix-up jobs around the home & garden.

### **SETS IN 5 MINUTES**

Dependent on the weather temperature at the time of use.

### **APPLICATIONS:**

Just the right amount of product for the small fix-up jobs around the home & garden such as:

- SMALL REPAIRS GROUTING PATCHING
- MODELLING HOBBIES BUILDING
- RENDERING BRICK & BLOCK LAYING



### **PRODUCT FEATURES:**

Sets in 5 minutes
Premium Quality
Australian Made
Professional Finish
High Performance Product
Ready-to-use just add water
Interior & Exterior Usage
Hard Wearing & Durable

### **DON'T FORGET:**

Excess water will decrease strength of mortar, concrete & render mixes

Always follow Safety, Usage & Handling Directions

Avoid creating & breathing in cement dust

Clean tools immediately after use with water

### **AVAILABLE IN:**

3kg and 10kg bags

### **DIRECTIONS FOR USE:**

Pre mixed & ready to use - just add water.

As a mix guide only - 1.5 litres of water to 10kg Australian Builders Quick Set Mortar dry mix product.

Mix thoroughly using the least amount of water to obtain the correct workability, (excess water will decrease strength of mortar & render mixes).

Mix only enough mortar that can be applied in less than 5 minutes. Time will vary dependent on air temperature, ie: the warmer the temperature, the quicker the setting process.

Don't overwork the surface area when floating or finishing. Use a steel trowel for a smooth finish or a wooden float trowel or broom for a textured finish

Always compact your mortar thoroughly.

Clean all tools with water immediately after use.

### **COVERAGE:**

10kg bag of mortar will lay 10 standard size bricks, 20mm thick mortar bed. (approx.)

# BUILDING PRODUCTS SUPPLIES - AUSTRALIAN BUILDERS HOME HANDYPAC QUICK-SET MORTAR MIX

## AUSTRALIAN BUILDERS™ HOME HANDYPAC™ QUICK-SET MORTAR















Important Consumer Information: Please read safe handling & usage advice before opening bag.

### **SAFE STORAGE:**

Portland Cement products should be stored in a dry dark environment, away from child access, preferably in a locked storage area.

Portland Cement when damp becomes Alkaline and exposure to it may be harmful to your skin and cause eye irritation.
Always read safety directions on packaging prior to opening bag and using product.


### **PRODUCT LIFE:**

Portland Cement products when stored correctly will last up to 6 months from date of manufacture. Once opened the contents should be used the same day.

### **HANDY HINT:**

For best results only use clean water. Add water to mixture not mixture to water.

Avoid working in excessive heat or cold temperatures.
Optimum working temperature is between 15-30° Celsius.



Contents: Portland Cement chemicals <60%. Crystalline Silica <1%. Non-hazardous ingredients to 100%.

Note: Crystalline Silica, (quartz), is present as an impurity.

Risk: Cement dust may cause respiratory, skin and eye irritation.

Wet cements can be irritating and corrosive to the eyes and skin; and may cause skin sensitisation (dermatitis). Repeated inhalation of dust containing crystalline silica may cause bronchitis, silicosis (scarring of the lung) and lung cancer, & increases the risk of Scleroderma.

Safety: Avoid contact with eyes and skin from both wet and dry cement. Do not breathe in dust. Wear suitable protective clothing, including gloves or barrier cream, foot wear and eye protection. Wear a P1 or P2 dust mask suitable for particulates when exposed to dust. When cutting or abrading concrete keep it wet with water to avoid creation of hazardous dust. Always wear suitable protective clothing and respiratory protection. Wash thoroughly after handling. Wash work clothes regularly.

First Aid: Irrigate eyes with plenty of water for 15 minutes and seek medical attention. If inhaled remove from dusty area. Seek medical attention if symptoms persist. Wash skin with water.

Spills/Leaks: Keep out of sewers and storm water.

Disposal: Follow above safety instructions and collect in containers for disposal as trade waste in accordance with local authority guidelines.

Manual Handling: Cement bags (16-40kg) are heavy, lifting them without due care and attention can result in personal injury. Unless you are trained in manual handling of heavy loads, it is best you share the load with another person.

DISCLAIMER: Building Products Supplies Pty Ltd products are premium quality and when used in accordance with directions, will produce consistent excellent results. However Building Products Supplies Pty Ltd accepts no responsibility for end-users inappropriate usage or faulty workmanship.





### **PROUDLY AUSTRALIAN MADE**

Additional consumer information is listed in the material data sheet for this product, available from the manufacturer: