

Landscape Chalk



Dy-Mark's Landscape Chalk is ideal for temporary marking on concrete, pavement, gravel, grass and other areas. The fast dry formula will last up to 30 days and is ideal for surveying, golf courses, excavation sites and construction sites. Landscape Chalk is suitable for use with the Long Arm Handle and 2 wheel Spot Marking Handle also available from Dy-Mark.

DIRECTIONS FOR USE

Preparation

Shake can for at least 20 seconds after the mixing ball begins to rattle.

Application

Hold can in the inverted position, approximately 15 – 20cm from surface. Spray thickness can be adjusted by moving closer or further away from the surface to be sprayed.

Removal

Landscape Chalk can be removed with the use of water, a stiff brush and detergent. Landscape Chalk can also be removed using a high pressure hose.

TECHNICAL DATA

Size:	350g Aerosol
Finish:	Matt
Colour:	Yellow, White
Consistency:	Liquid
Coverage:	Approximately 2½ sqm per can
Suitable Surfaces:	Concrete, bitumen, rock, grass and general broken ground
Drying Time:	10 minutes at 25°C
Ideal Application Temperature:	Between 5°C and 40°C

STORAGE

Store below 50°C. Do not store in direct sunlight or in vehicles under hot conditions. Protect aerosol cans against physical damage.

DISPOSAL

Aerosol should be completely emptied prior to disposal. Contents of can are under pressure. Do not puncture or incinerate even when empty. When empty, dispose of this container through an approved recycling scheme or seek advice from your local council regarding accepted disposal methods.

SAFETY INFORMATION

HIGHLY FLAMMABLE

Keep away from flame, heat and sources of ignition. Do not smoke and ensure adequate ventilation during use. Can be harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

Please note that the slip resistance and performance of this product depends on many factors outside the control of Dy-Mark; including surface preparation, correct application and environmental conditions.

Dy-Mark recommends a risk assessment prior to use to determine if the product is suitable to the:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants e.g. water, solvents or chemicals

For more information regarding the product's slip resistance, contact Dy-Mark Sales & Customer Support Centre on 1300 396 275.

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (**Australia: 13 11 26; New Zealand: 0800 764 766**).

Note: the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions.

Refer to Material Safety Data Sheet for more information.