

# Technical Data Sheet

## Slate Sealer

Sealers

7 Day Technical Support 1800 655 711

Testing Approvals: N/A

Description			
<p><b>Slate Sealer</b> is a high gloss, durable coating that seals and protects old and new slate surfaces while bringing out the natural colours. Recoating when necessary is no problem as the new coat will blend with the old to provide a new, hard wearing surface.</p>			
Features and Benefits			
<ul style="list-style-type: none"> <li>Enhances natural colour with a "wet look" finish</li> <li>Seals and protects from staining</li> </ul>		<ul style="list-style-type: none"> <li>Easy to re-coat</li> </ul>	
Area of Use			
<ul style="list-style-type: none"> <li>Natural slate floors</li> </ul>		<ul style="list-style-type: none"> <li>Natural slate surfaces</li> </ul>	
Technical Data			
Number of Coats:	2	Curing time:	7 days
Spreading Rate Per Coat:	6-10m <sup>2</sup> /L	Colour:	Clear
Wet Film Per Coat:	100-167 microns	Thinner:	Cleaning and Thinning Solvent
Recoat (@25°C):	2 hours	Shelf Life:	12 months
Application Guide			
<p>Surface Preparation</p> <ul style="list-style-type: none"> <li>Dampness in the slate could spoil the coating turning it milky. Allow 10 to 14 days after laying for slate and grout to dry. To test for moisture, tape a clear plastic sheet to the floor. If moisture appears on the underside of the plastic within 2 hours, the slate is too damp. Leave for a further 2 days and test again.</li> <li>Remove any dust or flaking slate, oils, grease, etc.</li> <li>Where the application is over a previous coating and if unsure of previous coating, a small test area should be undertaken to check compatibility.</li> </ul> <p>Application Procedure and Equipment</p> <ul style="list-style-type: none"> <li>Apply <b>Slate Sealer</b> by spray, brush or roller.</li> <li>One coat will darken the surface slightly and leave a low sheen finish. For a brilliant gloss, apply a 2nd coat after 1st coat had dried.</li> </ul>			
Precautions			
<ul style="list-style-type: none"> <li>Surfaces treated may become more slippery when wet.</li> </ul>			
Cleaning			
<ul style="list-style-type: none"> <li>Equipment can be cleaned with Cleaning and Thinning Solvent.</li> </ul>			

# Technical Data Sheet

## Slate Sealer

Sealers

7 Day Technical Support 1800 655 711

### Health and Safety

#### Safety Precautions

- Avoid breathing vapour. Wear organic vapour respirator meeting the requirements of AS1715 and AS1716.
- Provide good ventilation – open windows and doors and use circulating fans.
- Wear eye protection.
- Wear PVC or neoprene gloves. Avoid contact with skin.
- If product is splashed on skin it should be washed off with water before it can dry.
- Keep out of the reach of children.

#### First Aid

Swallowed: Contact a doctor or Poisons Information Centre. Do not induce vomiting. Give water to drink.

Eye: Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.

Skin: Remove contaminated clothing and gently flush affected areas with soap and water. Seek medical attention if irritation develops. Launder clothing before re-use.

Inhalation: Remove patient from exposure, into fresh air. Apply artificial respiration if patient has stopped breathing. Seek medical attention.

For detailed information refer to product label and the current Material Safety Data Sheet available from Crommelin.

In the case of an emergency please call the Poisons Information Centre on 13 11 26

### Transport and Storage

Sizes:	15L	Flash Point:	43°C
Weights:	15.5Kg	UN Number:	1263
Dangerous Goods Class:	3.2	Poisons Schedule:	5
Hazchem Code:	3(Y)E		

### Disclaimer

Crommelin® and other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks. Any advice, recommendation, information, assistance or service provided by Crommelin® in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.