

# Material Safety Data Sheet

CS: 1.5.32

Page: 1 of 5

Infosafe No™ LQ00C Issue Date : December 2011 ISSUED by BONDALL

Product Name **POT AND ORNAMENT SEALER AEROSOL**

Classified as hazardous

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name** POT AND ORNAMENT SEALER AEROSOL  
**Product Code** 94080 (400g)  
**Company Name** BONDALL PTY LTD (ABN 27 008 734 996)  
**Address** 113 Belmont Avenue  
Belmont  
WA 6104 Australia  
**Emergency Tel.** 0400 705 773 or Poisons Information Centre: 13 11 26  
**Telephone/Fax Number** Tel: (08) 6272 3800  
Fax: (08) 9277 4068  
**Recommended Use** Waterproofing surface treatment

## 2. HAZARDS IDENTIFICATION

**Hazard Classification** Classified as hazardous  
HAZARDOUS SUBSTANCE.  
DANGEROUS GOODS.  
Hazard classification according to the criteria of NOHSC.  
Dangerous goods classification according to the Australia Dangerous Goods Code.

**Risk Phrase(s)** Classified as hazardous  
R12 Extremely Flammable.

**Safety Phrase(s)** S16 Keep away from sources of ignition - No smoking.  
S24/25 Avoid contact with skin and eyes.  
S33 Take precautionary measures against static discharges.  
S9 Keep container in a well ventilated place.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>Name</u>	<u>CAS</u>	<u>Proportion</u>	<u>Hazard Symbol</u>	<u>Risk Phrase</u>
	Solvent naphtha (petroleum), medium aliphatic	64742-88-7	60-<100 %		
	Propane	74-98-6	5-15 %		
	Butane	106-97-8	5-15 %		
	Distillates, petroleum, hydrotreated light	64742-47-8	<10 %		
	Ingredients determined not to be hazardous.		Balance		

## 4. FIRST AID MEASURES

**Inhalation** Product contains asphyxiant gas. Avoid becoming a casualty - to protect rescuer, use air-viva, oxy-viva or one-way mask. Remove affected person from contaminated area - Apply artificial respiration if not breathing. Do not give direct mouth-to-mouth resuscitation. Resuscitate in a well-ventilated area. Seek IMMEDIATE medical attention.  
Note: in confined space - DO NOT ATTEMPT RESCUE WITHOUT ADEQUATE RESPIRATORY PROTECTION.

**Ingestion** Unlikely due to form of the product. If ingestion occurs, do not induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

**Skin** Remove contaminated clothing. Wash affected area thoroughly with soap and water Wash contaminated clothing before re-use or discard. Seek medical attention.

**Eye** If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

# Material Safety Data Sheet

CS: 1.5.32

Page: 2 of 5

Infosafe No™ LQ00C	Issue Date : December 2011	ISSUED by BONDALL
--------------------	----------------------------	-------------------

Product Name **POT AND ORNAMENT SEALER AEROSOL**

Classified as hazardous

**First Aid Facilities** Eye wash fountain, safety shower and normal washroom facilities.**Advice to Doctor** Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media** Use carbon dioxide, dry chemical, foam, water fog or water mist.**Hazards from Combustion Products** Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide, carbon dioxide.**Specific Hazards** This product is extremely flammable. Aerosol containers may explode and may become a projectile in a fire. Keep storage tanks, pipelines, fire-exposed surfaces etc cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Liquid content of containers will not support combustion.**Hazchem Code** 2YE**Precautions in connection with Fire** Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.**Unsuitable Extinguishing Media** Do not use water jet.

## 6. ACCIDENTAL RELEASE MEASURES

**Emergency Procedures** Extinguish or remove all sources of ignition and stop leak if safe to do so. Wear appropriate personal protective equipment and clothing to prevent exposure. Evacuate all unprotected personnel. Water spray or fog may be used to disperse/absorb vapour if any. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Place inert, non-combustible absorbent material onto liquid spillage. Collect residues and seal in labelled drums for disposal. If contamination of sewers or waterways occurs inform the local water authorities and waste management authorities in accordance with local regulations. Dispose of waste according to applicable local and national regulations.

## 7. HANDLING AND STORAGE

**Precautions for Safe Handling** EXTREMELY FLAMMABLE. VAPOUR OR GAS REDUCES OXYGEN FOR BREATHING. IN CONFINED SPACES MAY CAUSE ASPHYXIATION. Wear appropriate protective clothing and equipment to prevent inhalation, skin and eye exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. DO NOT store or use in confined spaces. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Keep containers closed when not in use. Build up of mists or vapours in the atmosphere must be prevented. Do NOT cut or heat containers as they may contain hazardous residues. Do not smoke. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.**Conditions for Safe Storage** Store in dry, well ventilated area away from sources of ignition, oxidising agents, foodstuffs, clothing and out of direct sunlight. Do not store above 50°C. Protect container against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Do NOT pressurise, cut or heat aerosol containers. Content is under pressure and can explode violently. For information on the design of the storeroom, reference should be made to Australian Standard AS 2278-2000 Non-refillable metal aerosol dispensers of capacity 50 mL to 1000 mL inclusive. Reference should also be made to all Local, State and Federal regulations.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Material Safety Data Sheet

CS: 1.5.32

Page: 3 of 5

Infosafe No™ LQ00C

Issue Date : December 2011

ISSUED by BONDALL

Product Name **POT AND ORNAMENT SEALER AEROSOL**

Classified as hazardous

<b>National Exposure Standards</b>	<p>No exposure value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC), Australia. However, the available exposure limits for ingredients are listed below:</p> <p>National Occupational Health And Safety Commission (NOHSC), Australia Exposure Standards:</p> <table><thead><tr><th rowspan="2">Substance</th><th colspan="2">TWA</th><th colspan="2">STEL</th><th rowspan="2">NOTICES</th></tr><tr><th>ppm</th><th>mg/m<sup>3</sup></th><th>ppm</th><th>mg/m<sup>3</sup></th></tr></thead><tbody><tr><td>Butane</td><td>800</td><td>1900</td><td>-</td><td>-</td><td>-</td></tr><tr><td>Propane</td><td>-</td><td>-</td><td>-</td><td>-</td><td>Asphyxiant</td></tr></tbody></table> <p>Asphyxiant gas, which when present in an atmosphere in high concentrations, leads to a reduction of oxygen concentration by displacement or dilution. It is not appropriate to recommend an exposure standard for each simple asphyxiant, rather it should be required that a sufficient oxygen concentration be maintained.</p> <p>The minimum oxygen content in air should be 19.5 per cent by volume under normal atmospheric pressure. Unconsciousness and death can rapidly ensue in an environment, which is deficient in oxygen.</p> <p>TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.</p> <p>STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.</p>	Substance	TWA		STEL		NOTICES	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	Butane	800	1900	-	-	-	Propane	-	-	-	-	Asphyxiant
Substance	TWA		STEL		NOTICES																		
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>																			
Butane	800	1900	-	-	-																		
Propane	-	-	-	-	Asphyxiant																		
<b>Biological Limit Values</b>	Not available																						
<b>Engineering Controls</b>	Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required.																						
<b>Respiratory Protection</b>	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapour/mist filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.																						
<b>Eye Protection</b>	Safety glasses with side shields or goggles as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.																						
<b>Hand Protection</b>	Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.																						
<b>Body Protection</b>	Suitable protective clothing should be worn e.g. cotton overalls buttoned at neck and wrist. When large quantities are handled the use of chemical resistant apron and safety boots is recommended.																						

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Clear liquid in an aerosol pressure pack
<b>Odour</b>	Hydrocarbon solvent odour
<b>Melting Point</b>	Not available
<b>Boiling Point</b>	Not available
<b>Solubility in Water</b>	Not available
<b>Specific Gravity</b>	0.9
<b>pH Value</b>	Not available
<b>Vapour Pressure</b>	Not available

# Material Safety Data Sheet

CS: 1.5.32

Page: 4 of 5

Infosafe No™ LQ00C	Issue Date : December 2011	ISSUED by BONDALL
--------------------	----------------------------	-------------------

Product Name **POT AND ORNAMENT SEALER AEROSOL**

Classified as hazardous

<b>Vapour Density (Air=1)</b>	Not available
<b>Evaporation Rate</b>	Not available
<b>Flash Point</b>	Not available
<b>Flammability</b>	Extremely flammable
<b>Auto-Ignition Temperature</b>	Not available
<b>Flammable Limits - Lower</b>	Not available
<b>Flammable Limits - Upper</b>	Not available

## 10. STABILITY AND REACTIVITY

<b>Chemical Stability</b>	Stable under normal conditions of storage and handling.
<b>Conditions to Avoid</b>	Heat, direct sunlight, open flames or other sources of ignition.
<b>Incompatible Materials</b>	Strong oxidisers
<b>Hazardous Decomposition Products</b>	Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
<b>Hazardous Polymerization</b>	Will not occur.

## 11. TOXICOLOGICAL INFORMATION

<b>Toxicology Information</b>	No data available for this material.
<b>Inhalation</b>	May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea and vomiting. Inhalation of product vapours may cause irritation of the nose, throat and respiratory system. Propane and Butane are asphyxiant gases which when present in an atmosphere in high concentration, leads to reduction of oxygen concentration by displacement or dilution. Symptoms include decreased visual acuity, decreased coordination and judgment, headache, dizziness, confusion, drowsiness, fatigue, shortness of breath, muscular weakness, convulsions, unconsciousness, coma and eventually death.
<b>Ingestion</b>	Unlikely to occur due to physical state of the product. However, if ingested, may irritate the gastric tract causing nausea and vomiting.
<b>Skin</b>	May be irritating to skin. Skin contact may cause redness, itching and swelling.
<b>Eye</b>	Irritating to eyes. On eye contact this product can cause tearing, stinging, blurred vision, and redness.
<b>Chronic Effects</b>	Prolonged or repeated skin contact may cause defatting leading to drying and cracking of skin and dermatitis. Prolonged inhalation may cause central nervous system depression with symptoms including dizziness, drowsiness, nausea and headaches. Chronic exposure may have adverse effects on the central nervous system, liver and kidneys.

## 12. ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	Not available
<b>Persistence / Degradability</b>	Not available
<b>Mobility</b>	Not available
<b>Environ. Protection</b>	Do not discharge this material into waterways, drains and sewers.

## 13. DISPOSAL CONSIDERATIONS

<b>Disposal Considerations</b>	Dispose of waste according to applicable local and national regulations. Do not cut, puncture or weld on or near containers. Empty containers may contain
--------------------------------	---

# Material Safety Data Sheet

CS: 1.5.32

Page: 5 of 5

Infosafe No™ LQ00C	Issue Date : December 2011	ISSUED by BONDALL
--------------------	----------------------------	-------------------

Product Name **POT AND ORNAMENT SEALER AEROSOL**

Classified as hazardous

hazardous residues. Empty the container completely before disposal.  
Contaminated containers must not be treated as household waste. Advise flammable nature.

## 14. TRANSPORT INFORMATION

**Transport Information** This material is classified as a Division 2.1 (Flammable Gases) Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road or Rail. ( 7th edition)  
Division 2.1 Dangerous Goods are incompatible in a placard load with any of the following:  
- Class 1, Explosives  
- Division 2.2 Non-flammable, Non toxic gas that have a subsidiary risk 5.1 except when all are packed in cylinders or pressure drums not exceeding 500L capacity.  
- Class 3, Flammable Liquids, if both the Division 2.1 and Class 3 dangerous goods are in tanks or other receptacles with a capacity individually exceeding 500L.  
- Division 4.1, Flammable Solids  
- Division 4.2, Spontaneously Combustible Substances  
- Division 4.3, Dangerous When Wet Substances  
- Division 5.1, Oxidising Agents  
- Division 5.2, Organic Peroxides  
- Class 7, Radioactive Substances

**U.N. Number** 1950

**Proper Shipping Name** AEROSOLS

**DG Class** 2.1

**Hazchem Code** 2YE

**EPG Number** 2D1

**IERG Number** 49

## 15. REGULATORY INFORMATION

**Regulatory Information** Classified as Hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC), Australia.  
Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Poisons Schedule** Not Scheduled

**Hazard Category** Extremely Flammable

## 16. OTHER INFORMATION

**Date of preparation or last revision of MSDS** MSDS Created: December 2011

**Contact Person/Point** Chemist: Tel No: (08) 6272-3800  
Emergency: Tel No: 0400 705 773  
...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.  
The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.