

Technical Data Sheet

Water Based Slate Sealer

Sealers

7 Day Technical Support 1800 655 711

Testing Approvals: N/A

Description

Water Based Slate Sealer is quick drying, enhances the natural colour of slate and provides a tough stain-resistant finish. **Water Based Slate Sealer** avoids the discomfort and inconvenience of the strong odours and fumes associated with traditional solvent borne sealers.

Features and Benefits

- | | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> • No objectionable solvent odours • Durable and long lasting • Good resistance to water, detergents, oils, mild acids and alkalis | <ul style="list-style-type: none"> • Excellent adhesion • Suitable for interior and exterior use • Quick drying • Can be re-coated in future years (no stripping required) |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Area of Use

- | | |
|-----------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> • Interior living areas • Outdoor entertaining areas | <ul style="list-style-type: none"> • Commercial areas (i.e. retail, food areas, etc.) |
|-----------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|

Technical Data

Number of Coats:	2-3	Recoat (@25°C):	30 minutes
Spreading Rate Per Coat		Curing time:	7 Days
1 st Coat:	12-14m ² /L	Colour:	Clear
2 nd Coat:	12-14m ² /L	Thinner:	Water
Wet Film Per Coat:	Various	Shelf Life:	12 months

Application Guide

Surface Preparation

- Ensure surfaces that have been in use are thoroughly cleaned with a suitable detergent to remove traces of oil and grease. The level of cleaning will determine the final appearance and product performance that will be achieved. Allow the surface to dry before application.
- Remove all surface dirt and dust.
- Prior to application, the product must be applied to a small test area to assess the desired finish, gloss and degree of slip-resistance.

Application Procedure and Equipment

- **Water Based Slate Sealer** can be applied by brush, roller or spray. Apply in thin but even wet coats. Do not attempt to achieve too high a film thickness in one coat.

Precautions

- **Water Based Slate Sealer** may become slippery when wet.
- Do not use if temperature is below 10°C, relative humidity is above 85% or rain is imminent.
- Do not use solvent borne adhesives or topcoats over **Water Based Slate Sealer**.

Technical Data Sheet

Water Based Slate Sealer

Sealers

7 Day Technical Support 1800 655 711

Cleaning

- Wash all equipment with water before product dries.

Health and Safety

Safety Precautions

- Provide good ventilation – open windows and doors and use circulating fans.
- If product is splashed on skin it should be washed off with water before it can dry.
- Wear gloves and eye protection during application.

First Aid

Swallowed: Contact a doctor or Poisons Information Centre. Do not induce vomiting. Give water to drink.

Eye: Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.

For detailed information refer to product label and the current Material Safety Data Sheet available from Crommelin.

In the case of an emergency please call the Poisons Information Centre on 13 11 26

Transport and Storage

Sizes:	4L	Flash Point:	N/A
Weights:	4.5Kg	UN Number:	N/A
Dangerous Goods Class:	N/A		

Disclaimer

Crommelin® and other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks. Any advice, recommendation, information, assistance or service provided by Crommelin® in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.