

# SIKKENS CETOL FILTER 7

Chemwatch Material Safety Data Sheet  
Issue Date: 10-Sep-2008  
NC317TCP

CHEMWATCH 6554-73  
Version No:5  
CD 2008/3 Page 1 of 19

---

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

### PRODUCT NAME

SIKKENS CETOL FILTER 7

### SYNONYMS

"Alkyd Resin"

### PRODUCT USE

Solvent borne coating for exterior use.

### SUPPLIER

Company: Tenaru Timber & Finishes Pty Ltd

Address:

184- 186 Campbell Street

Surry Hills

NSW, 2010

AUS

Telephone: +61 2 9360 4500

Telephone: 1300 745 356

Fax: +61 2 9360 1924

---

## Section 2 - HAZARDS IDENTIFICATION

---

### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.**

COMBUSTIBLE LIQUID, regulated under AS1940 for Bulk Storage purposes only.



### POISONS SCHEDULE

S5

### RISK

Risk Codes

R43

R65

R67

Risk Phrases

May cause SENSITISATION by skin contact.

HARMFUL - May cause lung damage if swallowed.

Vapours may cause drowsiness and dizziness.

### SAFETY

Safety Codes

S23

S25

S36

S51

S09

Safety Phrases

Do not breathe gas/ fumes/ vapour/ spray.

Avoid contact with eyes.

Wear suitable protective clothing.

Use only in well ventilated areas.

Keep container in a well ventilated place.

continued...

# SIKKENS CETOL FILTER 7

## Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 2 of 19

## Section 2 - HAZARDS IDENTIFICATION

S401	To clean the floor and all objects contaminated by this material use water and detergent.
S07	Keep container tightly closed.
S13	Keep away from food drink and animal feeding stuffs.
S26	In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.
S46	If swallowed IMMEDIATELY contact Doctor or Poisons Information Centre (show this container or label).

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
isoparaffins petroleum hydrotreated HFP	64742-47-8.	25-50
petroleum distillates HFP	64742-48-9.	<25
Tinuvin 384	127519-17-9	<2.5

## Section 4 - FIRST AID MEASURES

### SWALLOWED

- If swallowed do NOT induce vomiting.
  - If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
  - Observe the patient carefully.
  - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
  - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
  - Seek medical advice.
- Avoid giving milk or oils.  
Avoid giving alcohol.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

### EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

continued...

# SIKKENS CETOL FILTER 7

Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 3 of 19

Section 4 - FIRST AID MEASURES

## NOTES TO PHYSICIAN

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology].

## Section 5 - FIRE FIGHTING MEASURES

### EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

### FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include: carbon dioxide (CO<sub>2</sub>),

other pyrolysis products typical of

burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

continued...

# SIKKENS CETOL FILTER 7

Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 4 of 19

Section 5 - FIRE FIGHTING MEASURES

## FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

## HAZCHEM:

### Personal Protective Equipment

Gas tight chemical resistant suit.

## Section 6 - ACCIDENTAL RELEASE MEASURES

## EMERGENCY PROCEDURES

### MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

### MAJOR SPILLS

Chemical Class: aliphatic hydrocarbons

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
LAND SPILL - SMALL				
cross- linked polymer - particulate	1	shovel	shovel	R, W, SS
cross- linked polymer - pillow	1	throw	pitchfork	R, DGC, RT
wood fiber - pillow	2	throw	pitchfork	R, P, DGC, RT
treated wood fibre- pillow	2	throw	pitchfork	DGC, RT
sorbent clay - particulate	3	shovel	shovel	R, I, P
foamed glass - pillow	3	throw	pitchfork	R, P, DGC, RT

### LAND SPILL - MEDIUM

cross- linked polymer - particulate	1	blower	skiploader	R, W, SS
-------------------------------------	---	--------	------------	----------

continued...

# SIKKENS CETOL FILTER 7

## Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 5 of 19

### Section 6 - ACCIDENTAL RELEASE MEASURES

cross- linked polymer - pillow	2	throw	skiploader	R, DGC, RT
sorbent clay - particulate	3	blower	skiploader	R, I, P
polypropylene - particulate	3	blower	skiploader	W, SS, DGC
expanded mineral - particulate	4	blower	skiploader	R, I, W, P, DGC
polypropylene - mat	4	throw	skiploader	DGC, RT

#### Legend

DGC: Not effective where ground cover is dense

R; Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT: Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988.

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

### Section 7 - HANDLING AND STORAGE

#### PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/sec until fill pipe submerged to twice its diameter, then  $\leq 7$  m/sec).
- Avoid splash filling.
- Do NOT use compressed air for filling discharging or handling operations.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

continued...

# SIKKENS CETOL FILTER 7

## Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 6 of 19

## Section 7 - HANDLING AND STORAGE

- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

### SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

### STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents.

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

---

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### EXPOSURE CONTROLS

The following materials had no OELs on our records

- isoparaffins petroleum hydrotreated HFP:
- petroleum distillates HFP:
- Tinuvin 384:

CAS:64742- 47- 8

CAS:64742- 48- 9 CAS:64742- 88- 7

CAS:127519- 17- 9

### MATERIAL DATA

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

continued...

# SIKKENS CETOL FILTER 7

## Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 7 of 19

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

### INGREDIENT DATA

ISOPARAFFINS PETROLEUM HYDROTREATED HFP:

PETROLEUM DISTILLATES HFP:

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

ISOPARAFFINS PETROLEUM HYDROTREATED HFP:

for petroleum distillates:

CEL TWA: 500 ppm, 2000 mg/m<sup>3</sup> (compare OSHA TWA).

REL TWA: 300 ppm [EXXON]

PETROLEUM DISTILLATES HFP:

NOTE L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. European Union (EU) List of Dangerous Substances (Annex I) - up to the 29th ATP.

CEL TWA: 100 ppm, 525 mg/m<sup>3</sup> - as Stoddard solvent CCINFO 1441735 - [Shell]

TINUVIN 384:

No exposure limits set by NOHSC or ACGIH.

## PERSONAL PROTECTION

### EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal

continued...

# SIKKENS CETOL FILTER 7

Chemwatch Material Safety Data Sheet  
Issue Date: 10-Sep-2008  
NC317TCP

CHEMWATCH 6554-73  
Version No:5  
CD 2008/3 Page 8 of 19

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

### HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
  - Wear safety footwear or safety gumboots, eg. Rubber.
- Suitability and durability of glove type is dependent on usage. Factors such as:
- frequency and duration of contact,
  - chemical resistance of glove material,
  - glove thickness and
  - dexterity,
- are important in the selection of gloves.

### OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

### RESPIRATOR

Respiratory protection may be required when ANY "Worst Case" vapour-phase concentration is exceeded (see Computer Prediction in "Exposure Standards").

Protection Factor	Half- Face Respirator	Full- Face Respirator
10 x ES	A- P- - AUS	-
	A- P- - PAPR- AUS	
50 x ES	Air- line*	-
100 x ES	-	A- P- - 3
100+ x ES	-	Air- line**

\* - Continuous-flow; \*\* - Continuous-flow or positive pressure demand  
^ - Full-face.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

### ENGINEERING CONTROLS

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25- 0.5 m/s (50- 100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift,	0.5- 1 m/s (100- 200 f/min.)

continued...



# SIKKENS CETOL FILTER 7

Chemwatch Material Safety Data Sheet  
Issue Date: 10-Sep-2008  
NC317TCP

CHEMWATCH 6554-73  
Version No:5  
CD 2008/3 Page 9 of 19

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

plating acid fumes, pickling (released at low velocity into zone of active generation)  
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).

1- 2.5 m/s (200- 500 f/min.)

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only.
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Liquid; does not mix with water.

### PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

Molecular Weight: Not Applicable  
Melting Range (°C): Not Available  
Solubility in water (g/L): Immiscible  
pH (1% solution): Not Applicable  
Volatile Component (%vol): Not Available  
Relative Vapour Density (air=1): Not Available  
Lower Explosive Limit (%): Not Available  
Autoignition Temp (°C): Not Available  
State: Liquid

Boiling Range (°C): Not Available  
Specific Gravity (water= 1): 0.891  
pH (as supplied): Not Applicable  
Vapour Pressure (kPa): Not available  
Evaporation Rate: Not Available  
Flash Point (°C): 62 (CC)  
Upper Explosive Limit (%): Not Available  
Decomposition Temp (°C): Not Available  
Viscosity: 202 cSt@40°C

continued...

# SIKKENS CETOL FILTER 7

Chemwatch Material Safety Data Sheet  
Issue Date: 10-Sep-2008  
NC317TCP

CHEMWATCH 6554-73  
Version No:5  
CD 2008/3 Page 10 of 19

---

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

---

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

---

## Section 11 - TOXICOLOGICAL INFORMATION

---

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733).

Accidental ingestion of the material may be damaging to the health of the individual.

Ingestion of petroleum hydrocarbons can irritate the pharynx, oesophagus, stomach and small intestine, and cause swellings and ulcers of the mucous. Symptoms include a burning mouth and throat; larger amounts can cause nausea and vomiting, narcosis, weakness, dizziness, slow and shallow breathing, abdominal swelling, unconsciousness and convulsions. Damage to the heart muscle can produce heart beat irregularities, ventricular fibrillation (fatal) and ECG changes. The central nervous system can be depressed. Light species can cause a sharp tingling of the tongue and cause loss of sensation there. Aspiration can cause cough, gagging, pneumonia with swelling and bleeding.

Considered an unlikely route of entry in commercial/industrial environments. The liquid may produce gastrointestinal discomfort and may be harmful if swallowed. Ingestion may result in nausea, pain and vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

##### EYE

There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

Direct eye contact with petroleum hydrocarbons can be painful, and the corneal epithelium may be temporarily damaged. Aromatic species can cause irritation and excessive tear secretion.

##### SKIN

Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

The material may accentuate any pre-existing dermatitis condition.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

##### INHALED

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhaling high concentrations of mixed hydrocarbons can cause narcosis, with nausea, vomiting and lightheadedness. Low molecular weight (C2-C12) hydrocarbons can irritate mucous membranes and cause incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and stupor. Massive exposures can lead to severe central nervous system depression, deep coma and death. Convulsions can occur due to brain irritation and/or lack of oxygen. Permanent scarring may occur, with epileptic seizures and brain bleeds occurring months after exposure.

continued...

# SIKKENS CETOL FILTER 7

Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 11 of 19

## Section 11 - TOXICOLOGICAL INFORMATION

Respiratory system effects include inflammation of the lungs with oedema and bleeding. Lighter species mainly cause kidney and nerve damage; the heavier paraffins and olefins are especially irritant to the respiratory system. Alkenes produce pulmonary oedema at high concentrations. Liquid paraffins may produce sensation loss and depressant actions leading to weakness, dizziness, slow and shallow respiration, unconsciousness, convulsions and death. C5-7 paraffins may also produce multiple nerve damage. Aromatic hydrocarbons accumulate in lipid rich tissues (typically the brain, spinal cord and peripheral nerves) and may produce functional impairment manifested by nonspecific symptoms such as nausea, weakness, fatigue, vertigo; severe exposures may produce inebriation or unconsciousness. Many of the petroleum hydrocarbons can sensitise the heart and may cause ventricular fibrillation, leading to death.

Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.

If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

Nerve damage can be caused by some non-ring hydrocarbons. Symptoms are temporary, and include weakness, tremors, increased saliva, some convulsions, excessive tears with discolouration and inco-ordination lasting up to 24 hours.

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

### CHRONIC HEALTH EFFECTS

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function.

Skin exposure may result in drying and cracking and redness of the skin. Chronic exposure to lighter hydrocarbons can cause nerve damage, peripheral neuropathy, bone marrow dysfunction and psychiatric disorders as well as damage the liver and kidneys.

Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].

### TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

#### ISOPARAFFINS PETROLEUM HYDROTREATED HFP:

No significant acute toxicological data identified in literature search.

#### PETROLEUM DISTILLATES HFP:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

#### TOXICITY

Oral (rat) LD50: >8.0 mL/Kg = 6288 mg/kg \* [Shell - Canada]

Dermal (rat) LD50: >4.0 mL/kg = 3144 mg/kg

Inhalation (rat) LD50: 1400 ppm/4h

data for CAS 64742-88-7 i.e. CCINFO record 1441735

#### IRRITATION

#### TINUVIN 384:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

#### TOXICITY

Oral (Rat) LD50: >2000 mg/kg \*

#### IRRITATION

Skin : Not irritating

Eye : Not irritating

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly

continued...

# SIKKENS CETOL FILTER 7

## Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 12 of 19

## Section 11 - TOXICOLOGICAL INFORMATION

sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. Non-sensitising in guinea pig skin assays \*

Oral toxicity: The material a single dose of 2000 mg/kg was administered by gavage to adult albino rats (Tif:RAI f(SPF)), 5 rats of each sex. The animals were observed for 14 days. There were no deaths. Clinical signs were observed for up to 4 days post-dosing and included piloerection, hunched posture, and dyspnea. Normal bodyweight gain was observed during the observation period. At necropsy, macroscopic examination showed normal morphology.

Dermal toxicity: The material was applied at a dose level of 2000 mg/kg (undiluted liquid) to the clipped skin of albino rats (Tif:RAI f(SPF)) under semioclusive dressing for 24 hours. Five rats of each sex were used. The animals were observed for a period of 14 days after dosing. There were no deaths. Clinical signs were apparent for up to 5 days post-dosing and included piloerection, abnormal body positions, and dyspnea. Normal bodyweight gain was observed during the observation period. At necropsy, macroscopic examination showed normal morphology.

Skin irritation: The potential for the material to cause skin irritation was studied in 3 female New Zealand white rabbits. An area was clipped free of hair on both flanks of the animals. The test article (0.5 mL undiluted liquid) was applied under occlusive dressing to the right flank, and the left flank served as a control. The dressing was removed after 4 hours and the application site was examined at 1, 24, 48 and 72 hours after removal of the dressing. Slight erythema was observed in all 3 animals and slight oedema in 1 animal at 1 hour. Only slight erythema was apparent in 2 of the animals at 24 hours and all signs had disappeared by 48 hours.

Eye irritation: Tinuvun 384 was tested for potential ocular irritant effects in 3 male New Zealand white rabbits. The test substance (0.1 mL undiluted liquid) was placed into the conjunctival sac of the left eye of each animal. The right eye served as a control. The eyes were examined at 1, 24, 48 and 72 hours after the instillation of TK 13336. Slight, diffused erythema and slight oedema of the conjunctiva were observed in all animals at 1 hour but this was reduced to only some hyperaemic blood vessels remaining from 24 hours onwards.

Repeat dose toxicity: There were no deaths or treatment-related clinical signs during this study. A decrease in the rate of bodyweight gain was observed in both the males and the females of the high dose group from weeks 2 to 4. Food consumption was also decreased in the high dose males during weeks 1 and 2 and in the females of this group throughout the treatment period.

Neurological investigation consisting of measurement of body temperature, forepaw and hindpaw grip strengths and landing foot splay was conducted 5 days prior to the treatment and on days 17, 28 and 52 of the study. This investigation did not reveal any treatment-related effects.

Haematology showed slight but dose-dependent decreases in red blood cell count, haemoglobin and haematocrit in the mid and high dose groups. These decreases were statistically significant in the high dose group.

However, the reticulocyte levels were not decreased, but increased in the high dose group, suggesting that erythropoiesis was not impaired in these animals. The number of platelets was increased in the mid and high dose males, and the prothrombin time was slightly increased in the high dose males.

These haematological parameters were comparable to control values by the end of the recovery period.

Clinical chemistry revealed a dose-dependent and statistically significant increase in the albumin to globulin ratio in the mid and high dose groups. This was mainly due to a decrease in globulin levels.

Cholesterol and triglyceride levels were slightly increased in the mid and high dose groups. Potassium levels were increased in the mid and high dose males. Increased alkaline phosphatase activities were measured in the mid and high dose group, being up to 2.5-fold higher than control levels in the high dose males. Aspartate aminotransferase activity was also slightly increased in the high dose group. These clinical chemistry parameters were comparable to control values at the end of the recovery period.

At necropsy, absolute and relative liver weights were increased in the mid dose males and in both sexes in the high dose group. Organ weights in at the end of the recovery period were comparable to controls.

Mutagenicity Assay in Bacteria : The potential for TK 13336 to cause point mutations was investigated in Salmonella typhimurium (strains TA98, TA100, TA1535 and TA1537) and Escherichia Coli (strain WP2uvrA) reverse mutation assays. A dose ranging study showed that concentrations of TK 13336 of up to 5,000 ig/0.1 mL were not cytotoxic toward TA100. Consequently, the dose levels were chosen as 312, 625, 1,250, 2,500 and 5,000 ig/0.1 mL. TK 13336 was found not to increase the number of revertant colonies of S. typhimurium or E. Coli at any of the dose levels, when tested both in the presence or absence of rat liver microsomes (S9). Positive controls used in the absence of S9 were 2-nitrofluorene (for TA98), sodium azide (for TA100 and TA1535), 9-aminoacridine (for TA1537) for S. typhimurium and 4-nitroquinoline-N-oxide for E. Coli. In the presence of S9, positive controls used were 2-aminoanthracene (for TA98, TA100 and TA1537),

continued...

# SIKKENS CETOL FILTER 7

Chemwatch Material Safety Data Sheet  
Issue Date: 10-Sep-2008  
NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 13 of 19

## Section 11 - TOXICOLOGICAL INFORMATION

cyclophosphamide (for TA1535) for *S. typhimurium* and 2-aminoanthracene for *E. Coli*.

## Section 12 - ECOLOGICAL INFORMATION

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some of the material will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions the material will degrade to water and carbon dioxide, while under anaerobic processes it will produce water, methane and carbon dioxide.

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

ISOPARAFFINS PETROLEUM HYDROTREATED HFP:

DO NOT discharge into sewer or waterways.

PETROLEUM DISTILLATES HFP:

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some of the material will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions the material will degrade to water and carbon dioxide, while under anaerobic processes it will produce water, methane and carbon dioxide.

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

Chemical analysis for all individual compounds in a petroleum bulk product released to the environment is generally unrealistic due to the complexity of these mixtures and the laboratory expense. Determining the chemical composition of a petroleum release is further complicated by hydrodynamic, abiotic, and biotic processes that act on the release to change the chemical character.

The longer the release is exposed to the environment, the greater the change in chemical character and the harder it is to obtain accurate analytical results reflecting the identity of the release. After extensive weathering, detailed knowledge of the original bulk product is often less valuable than current site-specific information on a more

continued...

# SIKKENS CETOL FILTER 7

Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 14 of 19

Section 12 - ECOLOGICAL INFORMATION

focused set of hydrocarbon components. Health assessment efforts are frequently frustrated by three primary problems: (1) the inability to identify and quantify the individual compounds released to the environment as a consequence of a petroleum spill; (2) the lack of information characterizing the fate of the individual compounds in petroleum mixtures; and (3) the lack of specific health guidance values for the majority of chemicals present in petroleum products. To define the public health implications associated with exposure to petroleum hydrocarbons, it is necessary to have a basic understanding of petroleum properties, compositions, and the physical, chemical, biological, and toxicological properties of the compounds most often identified as the key chemicals of concern.

Petroleum products released to the environment migrate through soil via two general pathways: (1) as bulk oil flow infiltrating the soil under the forces of gravity and capillary action, and (2) as individual compounds separating from the bulk petroleum mixture and dissolving in air or water. When bulk oil flow occurs, it results in little or no separation of the individual compounds from the product mixture and the infiltration rate is usually fast relative to the dissolution rate (Eastcott et al.

1989). Many compounds that are insoluble and immobile in water are soluble in bulk oil and will migrate along with the bulk oil flow. Factors affecting the rate of bulk oil infiltration include soil moisture content, vegetation, terrain, climate, rate of release (e.g., catastrophic versus slow leakage), soil particle size (e.g., sand versus clay), and oil viscosity (e.g., gasoline versus motor oil).

As bulk oil migrates through the soil column, a small amount of the product mass is retained by soil particles. The bulk product retained by the soil particles is known as "residual saturation."

Depending upon the persistence of the bulk oil, residual saturation can potentially reside in the soil for years. Residual saturation is important as it determines the degree of soil contamination and can act as a continuing source of contamination for individual compounds to separate from the bulk product and migrate independently in air or groundwater. Residual saturation is important as it determines the degree of soil contamination and can act as a continuing source of contamination for individual compounds to separate from the bulk product and migrate independently in air or groundwater. When the amount of product released to the environment is small relative to the volume of available soil, all of the product is converted to residual saturation and downward migration of the bulk product usually ceases prior to affecting groundwater resources. Adverse impacts to groundwater may still occur if rain water infiltrates through soil containing residual saturation and initiates the downward migration of individual compounds. When the amount of product released is large relative to the volume of available soil, the downward migration of bulk product ceases as water-saturated pore spaces are encountered. If the density of the bulk product is less than that of water, the product tends to "float" along the interface between the water saturated and unsaturated zones and spread horizontally in a pancake-like layer, usually in the direction of groundwater flow. Almost all motor and heating oils are less dense than water. If the density of the bulk product is greater than that of water, the product will continue to migrate downward through the water table aquifer under the continued influence of gravity. Downward migration ceases when the product is converted to residual saturation or when an impermeable surface is encountered.

As the bulk product migrates through the soil column, individual compounds may separate from the mixture and migrate independently. Chemical transport properties such as volatility, solubility, and sorption potential are often used to evaluate and predict which compounds will likely separate from the mixture. Since petroleum products are complex mixtures of hundreds of compounds, the compounds characterized by relatively high vapor pressures tend to volatilize and enter the vapor phase. The exact composition of these vapors depends on the composition of the original product. Using gasoline as an example, compounds such as butane, propane, benzene, toluene, ethylbenzene and xylene are preferentially volatilized. Because volatility represents transfer of the compound from the product or liquid phase to the air phase, it is expected that the concentration of that compound in the product or liquid phase will decrease as the concentration in the air phase increases.

In general, compounds having a vapor pressure in excess of 10-2 mm Hg are more likely to

continued...

# SIKKENS CETOL FILTER 7

## Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 15 of 19

## Section 12 - ECOLOGICAL INFORMATION

be present in the air phase than in the liquid phase. Compounds characterized by vapor pressures less than 10-7 mm Hg are more likely to be associated with the liquid phase. Compounds possessing vapor pressures that are less than 10-2 mm Hg, but greater than 10-7 mm Hg, will have a tendency to exist in both the air and the liquid phases.

Lighter petroleum products such as gasoline contain constituents with higher water solubility and volatility and lower sorption potential than heavier petroleum products such as fuel oil.

Data compiled from gasoline spills and laboratory studies indicate that these light-fraction hydrocarbons tend to migrate readily through soil, potentially threatening or affecting groundwater supplies. In contrast, petroleum products with heavier molecular weight constituents, such as fuel oil, are generally more persistent in soils, due to their relatively low water solubility and volatility and high sorption capacity.

Solubility generally decreases with increasing molecular weight of the hydrocarbon compounds. For compounds having similar molecular weights, the aromatic hydrocarbons are more water soluble and mobile in water than the aliphatic hydrocarbons and branched aliphatics are less water-soluble than straight-chained aliphatics. Aromatic compounds in petroleum fuels may comprise as much as 50% by weight; aromatic compounds in the C6-C13, range made up approximately 95% of the compounds dissolved in water.

Indigenous microbes found in many natural settings (e.g., soils, groundwater, ponds) have been shown to be capable of degrading organic compounds. Unlike other fate processes that disperse contaminants in the environment, biodegradation can eliminate the contaminants without transferring them across media.

The final products of microbial degradation are carbon dioxide, water, and microbial biomass. The rate of hydrocarbon degradation depends on the chemical composition of the product released to the environment as well as site-specific environmental factors.

Generally the straight chain hydrocarbons and the aromatics are degraded more readily than the highly branched aliphatic compounds. The n-alkanes, n-alkyl aromatics, and the aromatics in the C10-C22 range are the most readily biodegradable; n-alkanes, n-alkyl aromatics, and aromatics in the C5-C9 range are biodegradable at low concentrations by some microorganisms, but are generally preferentially removed by volatilization and thus are unavailable in most environments; n-alkanes in the C1-C4 ranges are biodegradable only by a narrow range of specialized hydrocarbon degraders; and n-alkanes, n-alkyl aromatics, and aromatics above C22 are generally not available to degrading microorganisms. Hydrocarbons with condensed ring structures, such as PAHs with four or more rings, have been shown to be relatively resistant to biodegradation. PAHs with only 2 or 3 rings (e.g., naphthalene, anthracene) are more easily biodegraded. PAHs with only 2 or 3 rings (e.g., naphthalene, anthracene) are more easily biodegraded. A large proportion of the water-soluble fraction of the petroleum product may be degraded as the compounds go into solution. As a result, the remaining product may become enriched in the alicyclics, the highly branched aliphatics, and PAHs with many fused rings.

In almost all cases, the presence of oxygen is essential for effective biodegradation of oil. Anaerobic decomposition of petroleum hydrocarbons leads to extremely low rates of degradation. The ideal pH range to promote biodegradation is close to neutral (6-8). For most species, the optimal pH is slightly alkaline, that is, greater than 7. The moisture content of the contaminated soil will affect biodegradation of oils due to dissolution of the residual compounds, dispersive actions, and the need for microbial metabolism to sustain high activity. The moisture content in soil affects microbial locomotion, solute diffusion, substrate supply, and the removal of metabolic by-products. Biodegradation rates in soils are also affected by the volume of product released to the environment. At concentrations of 1-0.5% of oil by volume, the degradation rate in soil is fairly independent of oil concentrations. However, as oil concentration rises, the first order degradation rate decreases and the oil degradation half-life increases. Ultimately, when the oil reaches saturation conditions in the soil (i.e., 30-50% oil), biodegradation virtually ceases.

Excessive moisture will limit the gaseous supply of oxygen for enhanced decomposition of petroleum hydrocarbons. Most studies indicate that optimum moisture content is within 50-70% of the water holding capacity.

All biological transformations are affected by temperature. Generally, as the temperature increases, biological activity tends to increase up to a temperature where enzyme

continued...

# SIKKENS CETOL FILTER 7

## Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 16 of 19

## Section 12 - ECOLOGICAL INFORMATION

denaturation occurs. The presence of oil should increase soil temperature, particularly at the surface. The darker color increases the heat capacity by adsorbing more radiation. The optimal temperature for biodegradation to occur ranges from 18 °C to 30 °C. Minimum rates would be expected at 5 °C or lower.

TINUVIN 384:

Marine Pollutant: Not Determined

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

for UV filters:

UV filters have been detected in surface water, wastewater and fish, and some of them are estrogenic in fish. At present, little is known about their additional hormonal activities in different hormonal receptor systems despite their increasing use and environmental persistence. Besides estrogenic activity, UV filters may have additional activities, both agonistic and antagonistic in aquatic organisms.

Systematic analysis of the oestrogenic, antioestrogenic, androgenic, and antiandrogenic activity was conducted using 18 UV filters and one metabolite in vitro at non-cytotoxic concentrations with recombinant yeast systems carrying either a human estrogen (hER) or androgen receptor (hAR). All 19 compounds elicited hormonal activities, surprisingly most of them multiple activities. Ten UV-filters having agonistic effects towards the hER.

Surprisingly, six UV filters with androgenic activities and many of them having

pronounced antioestrogenic and antiandrogenic activities. Seventeen

compounds inhibited

4,5-dihydrotestosterone activity in the hAR assay, while 14 compounds inhibited oestradiol activity in the hER assay, indicating antiandrogenic and antiestrogenic activity, respectively. In particular, the antiandrogenic activities of phenyl- and benzyl salicylate, benzophenone-1 and -2, and of 4-hydroxybenzophenone were higher than that of flutamide, a known hAR antagonist.

Although most of the UV filters exert hormonal effects at concentrations that are orders of magnitude higher than in the environment, wide distribution and exposure to UV filter mixtures may have environmental consequences due to additive effects. The UV filters 4-methylbenzylidene camphor, benzophenone-3, benzophenone-4, octyl methoxycinnamate, octocrylene and homosalate that repeatedly were detected in the aquatic environment, may contribute with their multiple hormonal activities in a complex manner to the mixture of endocrine disrupting chemicals already present in surface water and fish. For most of the UV filters with multiple hormonal activities residues in the aquatic environment and in biota are not yet known, and therefore their environmental relevance remains elusive. The fact that all 18 UV filters and one metabolite showed receptor ligand binding via transactivation – surprisingly most of them multiple bindings – reveals a complex picture of the hormonal activities of UV filters.

Petra Kunz and Karl Fent: Aquatic Toxicology Vol 79 pp 305-324 October 2006.

Benzotriazole derivatives have been implicated as possible carcinogens, endocrine disruptors, and plant hormone regulators, but the literature on their biological activity is dated and tenuous. Benzotriazoles as a class may interact with the P-450s. The P450s are important both for detoxifying a broad range of xenobiotics and for activating many compounds to carcinogens in mammalian systems. Benzotriazoles are recalcitrant molecules used as corrosion inhibitors in antifreeze and deicing formulations. Existing data for members of this category indicate that they are of low concern for mammalian toxicity, will partition to soil and water. Benzotriazoles have high stabilities both at high temperatures and in presence of UV light. These compounds present an environmental problem due to their toxicity to microorganisms and plants. Until now, there have not been reports revealing ways for treating waste streams containing benzotriazoles by conventional methods, due to the lack of microorganisms that can degrade most benzotriazoles. No evidence for anaerobic degradation of benzotriazole and its derivatives was observed for both batch and continuously fed anaerobic systems. Benzotriazoles show toxicity to anaerobic microbes at fairly low concentrations. Acute

continued...



# SIKKENS CETOL FILTER 7

## Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 17 of 19

## Section 12 - ECOLOGICAL INFORMATION

toxic responses to benzotriazoles have been observed in MICROTOX'M assays at concentrations less than 10 mg/L. Aquatic organisms are known to be sensitive to low levels of benzotriazoles, for instance for fish, LC50 is around 30 mg/L.

Benzotriazoles are nitrification inhibitors. Much fertilizer N applied to soils is in the form of ammonium or ammonium-producing compounds such as urea, and is usually oxidised quite rapidly to nitrate by nitrifying microorganisms in soil.

Benzotriazole has a toxic effect on plants. Several reports cited in an EPA (1977) document indicated that benzotriazole can produce distinct morphological changes in a variety of plants. Tomato plants were shown to be sensitive to both benzotriazole and benzothiadiazole. Benzotriazole has a structure that resembles auxin, which may account for its toxicity to plants. It may also be an analog of purines and indoles. Plant roots interact with organic pollutants and some of these contaminants can be phytotransformed.

Root uptake of 1-H-benzotriazole and its derivatives, tolyltriazole, 5-methyl benzotriazole, and 1-hydroxy benzotriazole was studied. At levels below the toxic threshold of about 100 mg/L, triazoles appear to be incorporated into plant tissue.

Plants actively take up the triazoles at a rate greater than predicted by transpiration stream-concentration factor and plant-water uptake.

Benzotriazoles have been observed to be readily degraded by a Fenton reaction in the presence of peroxide and iron. Certain fungi produce lignin peroxidase (Phanerochaete chrysosporium for example) and have been shown to degrade benzotriazoles.

## Section 13 - DISPOSAL CONSIDERATIONS

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction,
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

## Section 14 - TRANSPORTATION INFORMATION



continued...

# SIKKENS CETOL FILTER 7

## Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 18 of 19

## Section 14 - TRANSPORTATION INFORMATION

Labels Required: COMBUSTIBLE LIQUID, regulated under AS1940 for Bulk Storage purposes only.

### HAZCHEM:

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: UN, IATA, IMDG

## Section 15 - REGULATORY INFORMATION

### POISONS SCHEDULE: S5

### REGULATIONS

Sikkens Cetol Filter 7 (CAS: None):  
No regulations applicable

isoparaffins petroleum hydrotreated HFP (CAS: 64742-47-8) is found on the following regulatory lists;

- Australia Hazardous Substances
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- International Air Transport Association (IATA) Dangerous Goods Regulations
- International Council of Chemical Associations (ICCA) - High Production Volume List
- OECD Representative List of High Production Volume (HPV) Chemicals

petroleum distillates HFP (CAS: 64742-48-9) is found on the following regulatory lists;

- Australia Hazardous Substances
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- International Air Transport Association (IATA) Dangerous Goods Regulations
- International Council of Chemical Associations (ICCA) - High Production Volume List
- OECD Representative List of High Production Volume (HPV) Chemicals

petroleum distillates HFP (CAS: 64742-88-7) is found on the following regulatory lists;

- Australia Hazardous Substances
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- International Air Transport Association (IATA) Dangerous Goods Regulations
- International Council of Chemical Associations (ICCA) - High Production Volume List
- OECD Representative List of High Production Volume (HPV) Chemicals
- OSPAR List of Chemicals for Priority Action

Tinuvin 384 (CAS: 127519-17-9) is found on the following regulatory lists;

- Australia Hazardous Substances
- Australia Inventory of Chemical Substances (AICS)

## Section 16 - OTHER INFORMATION

### INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
petroleum distillates HFP	64742- 48- 9, 64742- 88- 7

### EXPOSURE STANDARD FOR MIXTURES

"Worst Case" computer-aided prediction of vapour components/concentrations:

Composite Exposure Standard for Mixture (TWA) (mg/m<sup>3</sup>): 525 mg/m<sup>3</sup>

If the breathing zone concentration of ANY of the components listed below is exceeded,

"Worst Case" considerations deem the individual to be overexposed.

Component	Breathing Zone ppm	Breathing Zone mg/m <sup>3</sup>	Mixture Conc: (%)
-----------	--------------------	----------------------------------	-------------------

Component	Breathing zone (ppm)	Breathing Zone (mg/m <sup>3</sup> )	Mixture Conc (%)
petroleum distillates HFP	100.00	525.0000	25.0

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

continued...

# SIKKENS CETOL FILTER 7

Chemwatch Material Safety Data Sheet

Issue Date: 10-Sep-2008

NC317TCP

CHEMWATCH 6554-73

Version No:5

CD 2008/3 Page 19 of 19

Section 16 - OTHER INFORMATION

---

[www.chemwatch.net/references](http://www.chemwatch.net/references).

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 10-Sep-2008

Print Date: 10-Sep-2008