



ARTIFICIAL GRASS ADHESIVE

DUNLOP® ARTIFICIAL GRASS ADHESIVE is a high strength all weather adhesive suitable for indoor and outdoor use.

With excellent water and heat resistance it will bond securely to a wide variety of substrates and is ideal for installations around swimming pools, balconies and outdoors which may be subject to moisture after installation.

SURFACE PREPARATION

Surfaces must be dry, smooth, clean and free of any contaminants that may limit adhesion to the subfloor.

Imperfections in the subfloor can be fixed using either DUNLOP® FLOOR LEVELLER or DUNLOP® FLOOR REPAIRERS. Refer to respective products for suitable substrate information and application instructions.

The adhesive should not be used in extremely hot or cold conditions (i.e. below 10°C or above 35°C).

APPLICATION

- 1 Apply adhesive to the surface being covered with a 3.2x1.6x3.2mm "V" notched trowel.
- 2 Spread only sufficient adhesive so that the adhesive can be covered with artificial grass before the adhesive dries.
- 3 When laying the artificial grass outdoors, make sure the weather conditions are conducive to laying, as the adhesive takes 4 hours to cure before water resistant and 48 hours before waterproof. It is advisable to use plastic sheeting to cover work areas if weather becomes unsettled.

COVERAGE

1L of DUNLOP® ARTIFICIAL GRASS ADHESIVE will cover approximately 3m². Coverage will vary depending on the condition of the subfloor and application technique.

CLEAN UP

Clean tools and equipment immediately after use, with mineral turps.

SHELF LIFE

12 months when stored in the original unopened container at 20°C.

SAFETY AND STORAGE

Store away from sparks, open flame, and out of direct sunlight. Avoid contact with eyes and skin. Wear solvent resistant gloves and safety glasses. Avoid breathing vapours, and use with adequate ventilation.

FIRST AID

If poisoning occurs, contact a doctor or the poisons information centre. Do not induce vomiting. Remove from contaminated area, apply artificial respiration if not breathing. If skin contact occurs, remove clothing, wash skin thoroughly and seek medical advice.

TECHNICAL DATA

Characteristic of Product:

Colour: Light Green

Characteristic of Mix

Mixing: Premixed

Mix S.G: 1.00

Application Properties (at 23°C and 50% relative humidity)

Drying time: 4 hours (water resistant)

48 hours (waterproof)

Application temperature: 10-35°C

DUNLOP GUARANTEE

Product is guaranteed for 10 years when installed to manufacturer's instructions.

USER NOTES

The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with DUNLOP product instructions and in applications for which they are intended.

Made under license

ARDEX AUSTRALIA PTY LTD. ABN 82 000 550 005
20 Powers Road, Seven Hills NSW 2147 Australia.
Ph: +61 2 9851 9199 Fax: +61 2 9674 5621

SALES OFFICES:

Sydney: Ph+61 2 9851 9100 Fax+61 2 9838 7970
Brisbane: Ph+61 7 3881 3888 Fax+61 7 3881 3188
Melbourne: Ph+61 3 9308 9255 Fax +61 3 9308 9332
Adelaide: Ph+61 8 8268 2511 Fax+61 8 8345 3207
Perth: Ph+61 8 9455 1644 Fax+61 8 9455 1227
Christchurch: Ph+64 3 384 3029 Fax+64 3 384 9779

Jan06_v1

TOLL FREE SERVICE:
1800 222 841(Aust) 0800 224 070 (NZ)

WEBSITE:
www.dunlopdij.com