



TRADE RANGE TRADE RANGE TRADE RANGE TRADE RANGE



Ardit Rapidset REPAIR MORTAR

ARDIT RAPIDSET REPAIR MORTAR is an extreme, rapid hardening construction mortar which is trafficable after just 45 minutes and ready for floor coverings after 2 hours. Ideal for filling cracks and holes over a variety of surfaces, it is also suitable for use internally around doors, windows and plumbing installations. Ideal for ramping from a feather edge to normal screed thicknesses.



APPLICATION RANGE

Suitable for repairing holes and cracks of any depth over the following surfaces: Concrete, Render, Screeds, Masonry and patching of Plasterboard, Timber, Fibre-Cement Sheet.

If DUNLOP RAPIDSET REPAIR MORTAR is to be used as a wear surface, a suitable covering or coating is required. This product is to be used as a repair mortar only. If a self-levelling cementitious material is required, use DUNLOP ARDIT FLOOR LEVELLER.

SURFACE PREPARATION

Surfaces must be solid, clean and free of wax, grease and all loose contaminating materials or coatings. Dense surfaces including plasterboard, timber and fibre-cement sheet should be primed with DUNLOP PRIMER and allowed to dry. Porous surfaces will not require priming. Direct to earth surfaces such as on-ground concrete slabs, must be protected against rising damp. For example, a plastic sheet below the surface. Alternatively, seal with 2 coats of Dunlop Damp-Proof Waterproofing onto concrete surface and broadcast sand over the second coat.

MIXING

IMPORTANT: The mixed material is only usable for up to 15 minutes depending on ambient temperature so ensure that the surface is prepared for immediate application. In a clean bucket, mix 140ml of clean water with 1kg of DUNLOP RAPIDSET REPAIR MORTAR to a smooth consistency, preferably using an electric mixing paddle. Only mix enough material that can be used within the 15 minute pot life.

APPLICATION

Use a trowel to apply the DUNLOP RAPIDSET REPAIR MORTAR to the surface and immediately smooth off. After approximately 15 minutes, trim off excess material and finish off with a wet trowel and use a sponge to eliminate trowel marks and obtain a smoother surface.

DRYING TIME

The DUNLOP RAPIDSET REPAIR MORTAR will set after 45 minutes of application after which it can be walked on. Floor coverings such as vinyl, carpet and tiles can be installed after 2 hours. High temperatures will accelerate the drying time whilst low temperatures will slow the hardening process.

COVERAGE

5kg of DUNLOP RAPIDSET REPAIR MORTAR will cover approximately 3m² at 1mm thickness or 1m² at 3mm thickness.

CLEAN UP

Clean all tools in water immediately after use.

SHELF LIFE

12 months when stored in a dry place, in original unopened packaging.

PRECAUTIONS

Do not apply in temperatures below 10°C or above 30°C. Low temperatures will extend the drying time of the mortar whilst high temperatures will shorten the pot life and drying time of the DUNLOP RAPIDSET REPAIR MORTAR.

* Not suitable for use as a wear surface without a suitable coating or floor covering such as ceramic tiles, vinyl, carpet or suitable paint. Not suitable for use in permanently wet areas.

SAFETY DATA

The presence of cement in the product gives an alkaline mortar which may cause some irritation if prolonged contact with skin takes place. Keep out of the reach of children. Use gloves to prevent skin irritation. Avoid inhaling dust by using a dust mask. Wash immediately with plenty of water if material enters the eyes. Additional information is in the Material Safety Data Sheet (MSDS) available at www.dunlopdia.com

DUNLOP GUARANTEE

Product is guaranteed for 10 years when installed to manufacturer's instructions.

TOLL FREE SERVICE

1800 222 841 (AU)
0800 224 070 (NZ)

www.dunlopdia.com

ARDEX Australia Pty Ltd ABN 82 000 550 005
7/20 Powers Rd, Seven Hills NSW 2147

ARDEX Australia Pty Ltd
NSW Ph (02) 9851 9199
VIC Ph (03) 8339 3100
QLD Ph (07) 3817 6000
SA Ph (08) 8406 2500
WA Ph (08) 9256 8600

ARDEX New Zealand Ltd
Ph (03) 373 6900

TOLL FREE SERVICE:
1800 222 841(Aust) 0800 224 070 (NZ)

www.dunlopdia.com