HEATSTRIP®

Heating with Style









Heatstrip Classic, the Ultimate in Outdoor Heating

The Heatstrip Classic is an Australian designed & engineered range of premium quality, stylish & slimline electric radiant heaters ideal for protected outdoor and indoor heating applications. This includes your alfresco and outdoor dining area, patio, pergola, verandah, garage and shed, as well as cafés, restaurants, factories, showrooms, warehouses etc.

- Stylish, slimline, unobtrusive design
- Efficient, cost effective electric heating
- Significant running cost savings compared to bottled gas heaters
- Radiant heat means gentle comfortable warmth
- Corrosion protected for even the toughest environment
- Easy DIY installation for 3 models and multiple mounting options
- 2 year residential warranty (I year commercial)

General Technical Data

Model	Bunnings Item No,			Current (Amps)	Dimensions (mm)	Weight (Kg)	Lead Length (mm)	Plug	Heating Area (m²)	Status
THH1500A	3170731	30c / hr	1500	6.3	924 x 165 x 48	5	1000	Yes	2-3	Stocked
THH1800A	3170732	36c / hr	1800	7.5	1104 x 165 x 48	6	1000	Yes	3-4	Stocked
THH2400A	3170733	48c / hr	2400	10	1364 x 165 x 48	7	1000	Yes	4-5	Stocked
THH3200A	3170734	64c / hr	3200	13.3	1774 x 165 x 48	9	500	No	5-6	Special Order

*Running costs based on \$0.20/kwH. Heating area is for a protected outdoor site

Minimum Mounting Height	Recommended Range	Maximum Height
2.1m	2.3m - 2.5m	2.7m

For higher ceiling, units can be lowered using chains & wires or optional bracket kits or use Heatstrip Max

Running Cost	Outdoor Gas Heater	Heatstrip Classic electric heater			
Running Cost		THH1500A	THH1800A	THH2400A	THH3200A
Per Hour*	\$2.77/hr	\$0.30/hr	\$0.36/hr	\$0.48/hr	\$0.64/hr

*Costs based on an electricity rate of 20.0 cents/kWh. Calculations of hourly running cost for outdoor gas heater is based on \$25.00 avergae to fill a 9kg gas bottle and average running time of 9 hours. \$25.00 / 9 hours = \$2.77 per hour

	Materials of Construction							
	High temperature ceramic coated extruded alloy							
	Mounting Option	ns Beam/Pole Mount Bracket	Flush Mount Enclosure	Extension Mount Bracket	Suspension Mount Bracket	Twin Mount Bracket		
	Included as Standard		Optional <i>I</i>	Accessories <i>(Sp</i>	ecial Order)			
	THH1500A		3170738	3170745 (300mm)	2170750			
del	THH1800A	0170740	3170740	3170746 (600mm)	3170750	0170750		
Mo	THH2400A	3170743	3170741	3170748 (900mm)	0170751	3170/52		
	THH3200A		3170742	3170749 (1200mm)	31/0/51			
Model	Standard THH1500A THH1800A THH2400A	3170743	3170738 3170740 3170741	3170745 (300mm) 3170746 (600mm) 3170748 (900mm)	3170750 3170751	3170752		

Table layout

Approximate number of heaters required to heat common residential table settings









THH2400







2 x THH1800

THH2400

THH3200



Heatstrip Max, Innovative, High Performance Electric Heating Technology

Heatstrip Max is an Australian designed and engineered range of high intensity electric, infra-red radiant heaters ideal for tough outdoor and indoor heating applications.

Heatstrip Max has been specifically designed where all others heaters have failed - a high temperature radiant heater with a unique low-glow, shatter proof heating element, perfect even for fully exposed locations. Applications include outdoor alfresco areas, balconies, pergolas, patios, verandahs, courtyards, garages, sheds, warehouses, showrooms, halls etc.

- High temperature electric radiant heater ideal for higher ceilings or more exposed locations
- Unique "low glow" incoloy element no more blinding light
- Significant running cost savings compared to bottled gas heaters
- Commercial grade quality and construction 2 year warranty
- Corrosion resistance provided by the anodized alloy casing
- 2 models DIY (THX 2400) or hard wired (THX 3600).

General Technical Data

Model	Bunnings Item No,	Running* Costs	Power (Watts)	Current (Amps)	Dimensions (mm)	Weight (kg)		Status
THX 2400	3170735	48c / hr	2400	10	854 x 170 x 80	6	Supplied with lead & plug-DIY	Stocked
THX 3600	3170736	72c / hr	3600	15	1184 x 170 x 80	8	Must be hard wired	Special Order

*Running costs based on \$0.20/kwH

Heated Area (m²)	Bunnings Item No,	Indoor Protected (m²)	Outdoor Enclosed (m²)	Outdoor Exposed (m²)
THX 2400	3170735	16	10	6
THX 3600	3170736	24	15	9

Running Cost	Cont	Outdoor Gas	Heatstrip Max electric heater			
	Heater	THX2400	THX3600			
Per Ho	ur*	\$2.77/hr	\$0.48/hr	\$0.72/hr		

*Costs based on an electricity rate of 20.0 cents/kWh. Calculations of hourly running cost for outdoor gas heater is based on \$25.00 avergae to fill a 9kg gas bottle and average running time of 9 hours. \$25.00 / 9 hours = \$2.77 per hour

Model	Bunnings Item No,	Min, Mounting Height	Recommended Height	Max, Height Outdoor	Max, Height Indoor
THX 2400	3170735	2.1m	2.3m to 2.8m	3.0m	3.5m
THX 3600	3170736	2.1m	2.3m to 2.8m	3.0m	3.5m
	For higher ceiling, units can be lowered using chains & wires or optional bracket kits				

Materials of Construction

Anodised alloy casing and end caps with chromed grille




Table layout

Approximate number of heaters required to heat common residential table settings

THX2400

THX3600



















THX3600

THX3600

THX3600



Which Product do I need?

Application	Heatstrip Classic (THH-A)	Heatstrip Max (THX)
Outdoor Heating – undercover, well protected area with ceiling height less than 2.7m (al-fresco, verandah, café)	\checkmark	\checkmark
Outdoor Heating – undercover, well protected area with ceiling height from 2.7m to 3.0m (al-fresco, verandah, café)		\checkmark
Outdoor Heating – exposed area (al-fresco, café, veradah, balcony)		\checkmark
Indoor insulated areas – commercial (classrooms, offices, nursing homes, hospitals) residential (shed, garage etc)	\checkmark	
Indoor open, un-insulated areas requiring spot heating - factory, halls, warehouse, workshop, sports facility	\checkmark	\checkmark

Optional Controller

- Simple On/Off function with LED indicators
- 3 Heat Settings High / Medium / Low
- Automatic timer 1/2/4 hour options
- Suitable for operation of single or multiple heaters
- Must be hard-wired. Max, 14 amp direct wire
- Not included as standard. Must be purchased separately

9 334038 002899

27 Rosalie Street, Springvale VIC 3171 Australia t: (03) 9562 3455 f: (03) 9548 3979



www.heatstrip.com.au

Maximum Mounting Height Options

Ceiling heights are very important when deciding on which Heatstrip is best.

ſlax	HEATSTRIP CLASSIC	HEATSTRIP MAX	2 Em 1
	×		3.5m + 3.0m
		Rede Manas. Backase Backase Annual Backase Backase Backase Backase	2.7m
	Flash from Supprotein Subscore Record Record		2.5 m
	Ideal Range		2.3m 2.1m
	* Heatstrip Max can be mounted up to * Above figures are based on protected		Minimum Mounting Hieght
5			
red ed	Mounted directly overhead is preferred and provides maximum coverage	Angled mounting from the wall or ceiling is possible with the standard bracket, however the heating area is reduced	

[F] /ThermofilmAustraliaPtyLtd e: sales@thermofilm.com.au