

Power Breezer **Titan**



O2 Titan



TECHNICAL
SPECIFICATIONS

TECHNICAL SPECIFICATIONS		
	VOLTS GOVT. GRADE PART NUMBER	VOLTS GOVT. GRADE PART NUMBER
	220V PB20-A-1-F	220V MG-AB20-A-1F
Cooling Ability	Up to 15°C (27°F)	Up to 15°C (27°F)
Area of Coverage (Optimal)	Up to 279m² (3,000 sq. ft.)	Up to 140m² (1,500 sq. ft.)
Effective Distance	Up to 24 meters (80 feet)	Up to 12.2 meters (40 feet)
Oscillation	Yes	Yes
Integrated Water Container	Yes - 303 liters (80 gallons) Hose connection not required.	Yes - 151 liters (40 gallons) Hose connection not required.
Operating Time	4-5 days running 8 hours a day	4-5 days running 8 hours a day
Effective Water Vaporization	0.4L-7.6L/Hour (0.1-2 Gallons/Hour)	0.4L-3.6L/Hour (0.195 Gallon/Hour)
Electric Consumption	Avg. 5 Amps, 1,100 Watts (220V Unit)	Avg. 4 Amps, 880 Watts (220V Unit)
Air Flow	23,786 m³/hr (14,000 CFM)	16,990 m³/hr (10,000 CFM)
Height	116.8cm (46") stored, 177.8cm (70") mounted	106cm (41.75") stored 161cm (63.3") mounted
Width	75cm (29.5")	67cm (26.3")
Depth	107cm (42") stored, 130.8cm (51.5") mounted	94cm (37.0") stored 112cm (44.1") mounted
Weight (without water)	99.8kg (220 lbs.)	80kg (176 lbs.)
Power Source	220V (Type G Plug)	220V (Type G Plug)
Motor	1 hp E	1 hp E
Technology	Unique atomization technology	Unique atomization technology
Highly durable casters	25.4cm (10") and 20cm (8") rugged locking wheels/casters	20.3cm (8") and 15.2cm (6") rugged wheels/locking casters
Hard case for shipping and transport	Yes - Integrated into design	Yes - Integrated into design
Certifications	OSHA Compliant, ETL Certified, NOM Certified, CE Compliant (220V unit) SASO Compliant, MIL-STD 810G	OSHA Compliant (ETL, NOM, CE, SASO, MIL-STD 810G Certifications Pending)
Warranty	2 Years	2 Years

