

RetractAway 40 and RetractAway 50 Installation Instructions

Your Austral RetractAway clothesline is designed to last a long time. It is important to follow these instructions so you will enjoy the benefits of a properly installed clothesline. Incorrect installation or operation could damage your line and/or void your guarantee. If at any time your clothesline fails to function correctly or if spare parts are required then call your state distributor listed on the warranty.

IMPORTANT

There is considerable stored energy in the RetractAway at all times. Under no circumstances should you dismantle the unit or allow the Draw Arm to return unassisted to the RetractAway.



Site Selection and Mounting Option - Figure 1 and 2

Select a suitable site and mounting option for your RetractAway. The maximum span between mounting surfaces for the RetractAway 40 is 8m and 10m for the RetractAway 50. Minimum extension for RetractAway 40 or 50 is 2m. Minimum recommended clearance either side of the clothesline is 0.5m for ease of use and to allow clothes to blow in the breeze.


Cord Height - Figure 2

For a RetractAway, recommended Cord height is 100-200mm above the user's head height. Consider 100mm for normal/easier accessibility (particularly if shoulder mobility is of concern). Consider 200mm for longer spans as the Cords take more weight and have more sag.


Retracting type clotheslines experience greater Cord sag due to their larger spans. Compared to unloaded cords, a 9m span with a 50kg load will sag approximately 500mm and a 6m span approximately 350mm.




Wall to Wall




Wall to Post



Post to Wall



Post to Post



Austral Products You'll Need

Wall to Wall	Wall to Post	Post to Wall	Post to Post
1x Retractable 40 or 50	1x Retractable 40 or 50 1x Post [^] 1x Socket*	1x Retractable 40 or 50 1x Mounting Bar [^] 1x Post [^] 1x Socket*	1x Retractable 40 or 50 1x Mounting Bar [^] 2x Posts [^] 2x Sockets*

[^] Posts and Mounting Bars are supplied with nuts and bolts to enable fastening to one another or to the Retractable or Catch
* Sockets are optional and allow Posts to be removable

Other Equipment You'll Need

Wall to Wall	Wall to Post	Post to Wall	Post to Post
4x Wall Fixings	2x Wall Fixings	2x Wall Fixings. Plated Post (bolt-down): 2x Fixings	No Wall Fixings needed. Plated Posts (bolt-down): 4x Fixings

Wall fixings aren't supplied due to variations in mount surfaces. For masonry walls use 8x75mm screws and 10x75mm plugs. For timber use 8x75mm screws. When fixing to cladding (weatherboard, fibro, blueboard etc) fix directly to the stud, otherwise support battens should be used.

For Plated Posts (bolt-down) use 8x75mm screws and 10x75mm plugs.

- All installations: Tape measure, level, pencil and scissors or knife.
- Wall Mount you'll also need: drill and 10mm drill bit (safety glasses recommended for masonry drilling)
- Post Mount you'll also need: shovel, concrete mix, drainage gravel (Socket install only), bucket, 2x 13mm spanners/shifters.

Installation Steps

Follow the steps in order, details of each step listed on following pages, also refer to install tips on pg 4.

Wall to Wall	Wall to Post	Post to Wall	Post to Post
- Mount Retractable to Wall - Mount Catch to Wall - Line Tensioning	- Mount Retractable to Wall - Mount Catch to Post - Post Install - Line Tensioning	- Mount Retractable to Post - Post Install - Mount Catch to Wall - Line Tensioning	- Mount Retractable to Post - Mount Catch to Post - Post Install - Line Tensioning

Mount Retractable to Wall - Figure 2a and 3


Position Retractable on wall so that mounting slots on either side are approximately 200mm above the users head height. Ensure Retractable is level. Mark wall through both slots. Drill a 10mm hole on each mark to suit the fasteners. Fix Retractable to wall ensuring supplied washers are between the heads of the fasteners and the slots.

Mount Catch to Wall - Figure 2a

Place the receiving Catch against the wall opposite the Retractable, ensure the Catch is centred to the Retractable. Position the top of the Catch 200mm above the users head height. Ensure the Catch is level. Mark the wall through both holes. Using the marks, drill two 10mm holes to suit fasteners. Fix receiving Catch to wall using the fasteners.

Mount Catch to Post - Figure 2b

Fix receiving Catch to Post with 8x65mm bolts supplied with Post. Fit black plastic End Cap to top of Post.



Mount RetractAway to Post - Figure 3 and 2b

Remove one of the black end caps from the Mounting Bar to retrieve the supplied nuts and bolts. Use the long bolts to fix the Mounting Bar to the Post. Feed the short bolts through the washers supplied with the RetractAway. Use the short bolts to fix the RetractAway to the Mounting Bar ensuring washers are between the bolt heads and the slots on the RetractAway.

Post Install

IMPORTANT: if digging is required, ensure the area is safe and clear of electrical, gas and plumbing services etc (refer to Dial Before You Dig (Aus), beforeUdig (NZ), any architectural drawings etc).

Measure out the distance you want the Post to be at (Figure 1 for minimum and maximum span distances). Ensure the position is centred to where the other end of the clothesline is / will be. Mark the Post's position on the ground.

Install Post and Ground

Socket

Figure 4a

Dig a hole 200mm in diameter and 560mm deep. Fill hole with gravel (approx. 100mm) until top lip of Socket sits just above ground level. Remove Socket from hole. The Socket has five pairs of indentations to mark height settings, use the Cord Height chart (Fig 4a) to select a suitable height. Fit the supplied Pin into the corresponding pair of holes on the Socket (use a hammer or similar to tap the Pin through the indentations). Put Socket back in hole. Insert Post into Socket. Add a further 50mm of drainage gravel into the hole around the sides of the Socket.

Install Post Into Soil

Figure 4b / 4c


Use the Cord Height chart (Fig 4b) to select a suitable height and corresponding Post Embedment. Dig a hole 200mm in diameter and deep enough to allow for the Post Embedment plus a further 50mm, depth should be at least 450mm. If Post Embedment is less than 400mm, concrete under Post will be greater than 50mm. If Post Embedment is less than 300mm then Y12 rebar (reinforcing steel) is required (Fig 4c), drill holes through base of Post to fit the rebar. If area has poor drainage, ie soil type is clay or Post is installed at bottom of a slope etc, consider adding drainage gravel under Post as per Socket install (Fig 4a).

Install Plated Post

(Bolt-Down Post)

Place Post over marked position. Ensure Post's rectangular base plate is facing the right way. The base plate has 4 holes (to adapt to various scenarios) but only 2 fixings, diagonal to each other, should be used (refer fastener TDS for more info). Use base plate as a template to mark where 2 drill holes will be. Move Post out of the way, Drill two 10mm holes. Place Post back in position. To plumb and stabilise Post, place a level on the side of the Post, then place packers under base plate as required (plumb the Post front to back and side to side). Insert and tighten fixings.

Figure 4



Post Install Continued - Mix and Pour Concrete

- Mix concrete in the ratio of 4 gravel, 2 sand and 1 cement or use premixed concrete bags. To hold the Post/Socket in place, the concrete must be mixed fairly dry but should still be wet enough that it sticks to itself when stirred, it should not crumble.
- Place the Post / Socket (with Post in it) in the hole. Ensure the RetractAway and/or Catch is facing the right way. Pour concrete to within 20mm from the top of the hole (finished ground level). Check the Post is plumb/vertical (front to back and side to side) using a spirit level. Use a crowbar or similar to ram the concrete tight so it holds the Post/Socket in place. Top up the concrete level so it remains at 20mm below ground level, check vertical and ram tight again, repeat. Fill last 20mm of hole with soil, press soil down gently with the heel of your shoe. Check vertical one last time. Leave concrete to set, DO NOT USE FOR 48 HOURS.

Line Tensioning

Only untie and tension one Cord at a time (Fig 5a / 5b). Cord tension will be lost and product damage may occur if multiple lines are untied at the same time. If Posts have been installed ensure concrete is set and dry before tensioning the lines. Extend the Draw Arm to the Catch (Fig 2). Starting on the middle line, un-cleat the Cord then pull the loose end and keep drawing the Cord through until the cylindrical Drum, which can be seen inside the RetractAway, has only three full rotations of Cord left on it. Re-cleat the Cord, snip off the excess cord allowing an 80mm tail from the cleat (Fig 5b) and fit it back into the Cord Tidy. Flick the RetractAway's Tension Lock to the locked position (Fig 3). Turn the Tension Knob firmly in a clockwise direction, 1 - 4 clicks (Fig 3). Continue tensioning by selecting an outer line, un-cleat the Cord then pull the loose end and keep drawing the Cord through until firm. Re-cleat the cord, snip off the excess and fit the tail back into the Cord Tidy. Repeat for the other outside line then the remaining 2 lines.

Retracting The Cord


Switch the Tension Lock to the unlocked position (Fig 3) before retracting the Cord back into the RetractAway, this ensures minimum wear on internal gears. If there is a lot of tension on the Cord, the Lock may be harder to move. To make it easier, take tension off the Lock by turning the Tension Knob clockwise a little with the right hand. Whilst doing this, switch the Lock to the unlocked position with your left hand. Then, unhook the Draw Arm from the Catch and slowly guide the Cord and Draw Arm back into the RetractAway.

Installation Tips

Larger Post Footings: Where there is concern about the stability of the ground surrounding the concrete footing (sand, loose or shifting soil etc) or the RetractAway covers a long span, over 6m, a larger concrete footing should be considered. To do this increase the hole size to 250-300mm diameter by 500-700mm deep. Y12 Rebar (12mm reinforcing steel, refer Fig 4c) should be used where the footing depth exceeds the Post Embedment by more than 150mm.

Hammer Drilling: Hammer drill bits often travel when starting a hole. Start slow, with firm pressure and without the hammer to create a small indentation, then increase speed and switch to hammer. After the first hole, recheck marks for remaining holes.

Lean Posts Back: Tension and load causes Posts to flex inwards. To compensate you may wish to lean the Post/s back 2-3 degrees, approximately when the edge of the bubble in the level touches the line (Fig 6). Consider how the post will look when both loaded and unloaded.



Install RetractAway Upside Down: If space is tight and mounting the RetractAway the right way up prevents access to the Tension Knob and Tension Lock (located on the right end of the RetractAway) then the RetractAway can be mounted upside down. However, please note the RetractAway has not been designed for this and performance may be reduced. If rain collects inside the RetractAway drill a 2mm drain hole on the underside centre of the RetractAway's metal skin.

Operation and Maintenance


Hang Long Items Near the Ends: Cord is lowest to the ground near the middle, hang longer items near the ends.

Rain and Wind can Indirectly Damage Your Clothesline: Washing soaked by rain is significantly heavier than spun dry washing and the resulting load may exceed the RetractAway's load rating resulting in damage to the clothesline. This can be further compounded by high winds blowing and buffeting the washing load around. Remove washing if rain is likely.

Socket Cap: Place the Socket Cap over the Socket whenever the Post is removed. Remove the Cap from the Socket when mowing. The hook on the Socket Cap allows it to be hung from the Cord when the Cap is not in use.

Cord Tension: Occasionally re-tension individual Cords as required.

Check Fixings: Occasionally check all nuts and bolts for tightness.



MANUFACTURER'S WARRANTY

Austral Clothes Hoists Pty Ltd ("Austral") provides the following warranty in relation to its Clothes Lines products ("Product").

WARRANTY

Subject to the exclusions below, Austral warrants:

- **for 12 months from date of purchase:** the repair or replacement, in its discretion, of any Product that fails to operate correctly due to faulty workmanship or defective materials. The "materials" includes the plastic components and cord.
- **for 10 years from date of purchase:** the repair or replacement, in its discretion, of any part of the tubular frame that is broken or distorted as a direct result of rust. The "tubular frame" comprises the circular, square or rectangular hollow steel frame on powder coated or galvanised Product.

The benefits of this warranty are in addition to the non-excludable rights and remedies imposed by Australian State and Federal legislation.

WARRANTY CLAIMS

To make a warranty claim, please contact your place of purchase or your local Distributor with details of the alleged defect and your original receipt as proof of purchase. Where it is deemed necessary, Austral will arrange for the inspection of your Product.

You must bear the cost of making the Warranty claim. Austral will bear the cost of repairing or replacing defective Product (including freight or postage of replacement Product).

WARRANTY EXCLUSIONS

Austral's Products are suitable for air drying purposes.

The Warranty does not cover:

- defects caused through abuse or misuse.
- incorrect adjustments or unauthorised repairs.
- defects caused by incorrect installation.
- Product damage or deterioration due to abnormal environmental conditions including storm damage, fire, wind, humidity, pressure, stress and similar.
- powder coat deterioration caused by exposure to sea air where the Product is installed in coastal areas.
- defects caused through normal wear and tear.
- defects caused through the installation or use of a clothesline cover or sunshade.

SPARE PARTS

Austral maintains stock of spare parts for a reasonable period of time. Spare parts may not be available for the entire duration of this Warranty.

Austral reserves the right to repair or replace defective Product with parts and components of similar quality, grade and composition where an identical part or component is not available.

Goods presented for repair may be replaced by refurbished goods of the same type rather than being repaired.

LIMITATIONS

Austral makes no express warranties or representations other than as set out in this warranty. The repair or replacement of the Product or part of the Product is the absolute limit of Austral's liability under this express warranty.

Distributor Contacts:

State:	Phone:	Address:
VIC & TAS	03 9799 8122	32-34 Hydrive Close, Dandenong South, VIC, 3175
NSW & ACT	02 9958 1533	PO Box 380, Cammeray, NSW, 2062
SA & NT	08 8337 4445	20 Sunbeam Road, Glynde, SA, 5070
WA	08 9455 1985	Unit 3, 12-14 Panama Street, Canning Vale, WA, 6155
QLD	07 5596 2520	8 / 24 Palings Court, Nerang, QLD, 4217

Contact your local Retailer or Distributor for Spare Parts, Accessories and Warranty claims.

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.