



Zinc Gal - Aerosol



Dy-Mark's Zinc-Gal is a zinc rich, high performance, corrosion inhibitive coating. Zinc-Gal is suitable for use on ferrous metals such as steel and iron. The product is quick drying has excellent adhesion to ferrous materials and provides galvanic corrosion resistance to rusting.

DIRECTIONS FOR USE

Preparation

Surface should be clean, dry and free from contaminants such as rust, oil, grease and dirt. Shake can for at least 20 seconds after the mixing ball begins to rattle (IMPORTANT as the contents have a high density). Shake the can occasionally during use.

Application: Hold can upright and spray, adjusting the nozzle to achieve the desired spray pattern.

TECHNICAL DATA

Size:	400g Aerosol
Finish:	Matt
Colour:	Grey
Consistency:	Heavy Liquid
Coverage:	Approximately 2 sqm per can (depending on the surface)
Suitable Surfaces:	Steel, iron
Drying Time:	5 minutes at 25°C
Temperature:	Between 10°C and 40°C

STORAGE

Store below 50°C. Do not store in direct sunlight or in vehicles under hot conditions. Protect aerosol cans against physical damage.

DISPOSAL

Aerosol should be completely emptied prior to disposal. Contents of can are under pressure. Do not puncture or incinerate even when empty. When empty, dispose of this container through an approved recycling scheme or seek advice from your local council regarding accepted disposal methods.

SAFETY INFORMATION

HIGHLY FLAMMABLE

Keep away from flame, heat and sources of ignition. Do not smoke and ensure adequate ventilation during use. Can be harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (Australia: 13 11 26; New Zealand: 0800 764 766).

Note: the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.