

**SOLVENTS & THINNERS**

# Diggers Xylene

## DESCRIPTION

Diggers Xylene is a specialty solvent for thinning and stripping sealers.

## TYPICAL USES

- Thinning for solvent based acrylic (SBA) sealers
- Stripping solvent based acrylic (SBA) sealers
- Removes grease, oil and dirt

## FEATURES

- High solvency power
- Mid-to-slow evaporation rate

## APPLICATION

### Thinning Sealers

- Always follow the manufacturer's directions when thinning sealers.

### Stripping Sealers

- Test a small area first before taking on the whole job. Saturate a lint free cloth and wipe the surface using a clean part of the cloth for each wipe. Do NOT use on painted surfaces or Perspex.

## SAFETY

Wear suitable protective clothing, gloves and eye / face protection when using this product.

### Typical Characteristics

Appearance .....colourless liquid  
 Specific Gravity..... 0.87  
 Flash Point.....26°C  
 Boiling Point.....136–145°C  
 Flammability Limit..... 1–7.1%  
 Auto Ignition Point....432–530°C

 **MSDS available**



Code	Pack Size	Unit Barcode	Carton Barcode	Ctn/Plt
16030-61DIGN	6 x 1 litre	9311052002098	19312852002018	96
16030-4DIG	4 x 4 litre	9311052002104	19312852002025	45
16030-20	1 x 20 litre	9312852002240	N/A	32

**QUEENSLAND**  
Tel +61 7 3308 5200  
Fax +61 7 3308 5201

**NEW SOUTH WALES**  
Tel +61 2 8709 9600  
Fax +61 2 9791 5066

**VICTORIA**  
Tel +61 3 9408 4144  
Fax +61 3 9408 4155

**SOUTH AUSTRALIA**  
Tel +61 8 8222 1333  
Fax +61 8 8260 7883

**WESTERN AUSTRALIA**  
Tel +61 8 9352 3000  
Fax +61 8 9352 3033

© Copyright Recochem Inc. All rights reserved. All content remains the property of Recochem Inc. All other trademarks mentioned are trademarks or registered trademarks of their respective owners. All text, images, graphics and PDF files are subject to the copyrights and intellectual property rights of Recochem Inc. Separate to the purpose of review and private use, this information cannot be used without written permission from Recochem. Information contained herein is for general information only and should not be used as an infallible to a product's specification and or performance.