



LiquidStone Pattern Tape

Used to create stencilled patterns on small concrete areas.

DESCRIPTION

Crommelin[®] LiquidStone Pattern Tape is a unique filament reinforced tape for creating stencilled patterns on small areas of concrete with Crommelin[®] LiquidStone Colour.

FEATURES AND BENEFITS

- High tack tape.
- Creates a stencilled pattern on concrete.

AREAS OF USE

LiquidStone Pattern Tape is suitable for use on:

- Walkways.
- Courtyards.
- Decorative Walls.
- Facades.

SUITABLE SUBSTRATES

LiquidStone Pattern Tape is suitable for use on the following surfaces:

- Concrete – cleaned and dry.
- Fibre Cement Cladding



SURFACE PREPARATION

Full surface preparation instructions can be found at www.crommelin.com.au/full-instructions/

Surfaces must be clean, sound and free from dust, grease, curing compounds, release agents, loose particles, efflorescence, concrete laitance or any other contaminants. Use Crommelin[®] DiamondCoat[®] Clean N Prep to remove grease, oils etc.

- **All surfaces to be coated must be dry.** A moisture test is required 100% of the time to ascertain if the substrate is dry enough to coat. Electronic moisture meters are recommended, however a simple test may be performed as per below.

Simple Moisture Test: Place a 300mm x 300mm piece of black plastic or rubber mat on the area to be coated at the hottest part of the day. After 2 hours, remove and inspect. If any condensation is present on the underside of the plastic, or the substrate has darkened, then it is too wet to coat. Be patient, allow to dry further and repeat test until no moisture is detected.

- If substrate is porous, ensure the surface has been suitably primed with **Crommelin[®] LiquidStone Surface Primer** and has sufficiently dried prior to application.

APPLICATION PROCESS

To create uniform and consistent patterns always ensure:

- The pattern is measured out and partially marked using a pencil or chalk first.
- The pattern tape should be applied in a progressive manner ensuring all edges are firmly adhered .i.e. start to finish.
- Once the second coat of Crommelin[®] LiquidStone has been applied, remove the tape immediately to ensure a clean edge is obtained.

SIZES

Crommelin[®] LiquidStone Pattern Tape is available in 45m roll.

RELATED PRODUCTS

- Crommelin[®] Moisture Meter.
- Crommelin[®] LiquidStone Surface Primer.
- Crommelin[®] LiquidStone Clear Coat.
- Crommelin[®] LiquidStone Colour.

TRANSPORT AND STORAGE

- | | | | |
|-----------------|--------------------|------------------------|-------------------------|
| • Size: 45m | • Weight: 85g | • Cool and Dry Storage | • UN Number: N/A |
| • DG Class: N/A | • Flash Point: N/A | • Hazchem Code: N/A | • Poisons Schedule: N/A |

Crommelin[®] and other marks followed by ® are registered trademarks.

Any advice, recommendation, information, assistance or service provided by Crommelin[®] in relation to its products or their use is given in good faith, however is provided without responsibility or liability.

Customers need to undertake their own assessment to determine the suitability of a product for the intended use. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs as required on the specific surface.

Crommelin[®] also reserves the right to update information without prior notice, to reflect ongoing research and product development.



7 Day Technical Support 1800 655 711

72 Division Street, Welshpool Western Australia 6106 T +61 8 9458 5711 F +61 8 9451 4749
service@crommelin.com.au www.crommelin.com.au