

VCM Manual Skylight Flat Roof

Main features

Smooth profile grey aluminium capping

Heavy duty seal for flat or low pitch roofs

Laminated double glazing as standard

NEAT™ coating on glass pane

6 sizes available

Insect screen and operating hook included as standard**

Interior white PVC frame



Construction


White PVC frame and sash components with extruded gaskets. White framed insect screen included as standard.

VCM needs a custom flashing made by roofer, see preparation guide overleaf.

Operation

VCM Skylights are manually operated. The VCM has a hook included which requires a rod control to wind the hook and open the sash, or for applications within reach, a winder handle can be used.**

High Performance Double Glazing as standard



§ VCM 4646 outer pane is 3.9mm.

Benefits:

- Radiant heat block: Complete window Glass only **approx 75%**
- UV Harmful rays block **approx 70%**
- Noise reduction factor[#] **approx 99%**
- WERS rating **32 decibels**
- Double layer of Low-E³ coating. **5 stars**
- 10 year warranty on insulated glass seal.
- Reduced cleaning frequency.

Australian Standard AS1288

Laminated glass must be used for skylights installed 3m or more above floor level (standard with VCM).

NEAT™ Photocatalytic Coating

- Silicone Dioxide/Titanium Dioxide coating reacts with the sun's UV rays to decompose surface organic dirt before rinsing away with the next shower of rain, thereby reducing cleaning frequency.

- The coating also makes the glass surface smoother, so water disperses evenly, sheets off, and evaporates quickly; thereby minimising water spotting on the pane.



* VELUX recommends VCM is installed with a slight pitch (e.g. 3°-5°) to help prevent condensation build-up and water ponding on the glass.
#Based on STC value tested to ISO/IEC 17025:2005.

10 YEAR WARRANTY
on skylights and glazing

3 YEAR WARRANTY
on blinds and accessories

VCM technical performance

Australian Standards

VELUX Skylights are tested and approved to the appropriate Australian Standards.

AS4285 SKYLIGHTS[±]
Cyclonic & Non-Cyclonic

AS1288 OVERHEAD GLAZING
Laminated inner pane

AS3959 BUSHFIRE
Attack Level 40[^]

AS1530.1: BCA BOUNDARY SEPARATION[†]
Class 1 & Class 10 buildings:
Within 900mm of a boundary wall
Class 2 to Class 9 buildings:
3 metres from a boundary wall^{^^}

VELUX Skylights are deemed non-combustible and thereby comply with BCA Fire Separation requirements.

± Tests performed on skylight installed with #8 roofing screws (not screws provided).

† CSIRO assessment report available on request. VELUX recommends consultation with relevant authority before work commences. Skylight assessed in closed position.

^ Roof pitch 0°-60° Skylight only. Custom-made flashing required. Skylight tested in closed position, additional mesh protection may be required for opening apertures (consult local council).

^^ Skylight cannot be closer than 3m unless the boundary is adjoining a road or public place. Consult BCA for further details.

Energy Rating

VCM Openable Skylights have been energy rated in accordance with the Skylight Energy Rating Scheme (WERS).

★★★★★ **Maximum 5 stars Summer Ratings**

4.5 out of 5 stars for Winter Rating.

4.5 out of 5 stars for Cool Daylight in Summer.

| Glazing type | 2004 |
|------------------------------|------------------|
| U-value (W/m ² K) | |
| Complete skylight | 2.9 [‡] |
| Glass only | 1.93 |

| Solar Heat Gain Co-efficient | |
|------------------------------|------|
| Complete skylight | 0.24 |
| Glass only | 0.28 |

| Visible Light Transmittance | |
|-----------------------------|------|
| Complete skylight | 0.55 |

| Luminous Efficacy (Ke = VT/SHGC) | |
|----------------------------------|------|
| Complete skylight | 2.29 |

All figures generated by AFRC accredited simulators. Figures based on complete skylight: nominal size 1140mm (W) x 1180mm (H).

‡ See required installation method overleaf.

**Winder handle and extension rods to be purchased separately. Details overleaf.

VCM Manual Skylight Flat Roof

Solar Powered Blockout blind



- Uses the sun's energy to power the built-in motor.
- Operated by wireless wall-mounted keypad (provided).
- Provides blockout from light.
- Colour: White on internal side. Silver coating on external side.
- Materials: Light-tight polyester with heat resistant coating. Aluminium side channels and top cover.
- Reduce light by approx 100%.
- Reduce heat by approx 40%.[^]
- Easy to fit using VELUX **Pick & Click!**[®] system.

Blinds sold separately.

Control options

Out of reach situations

ZCT 300 extension rod
Telescopic rod control (145cm in length, extendable up to 285cm)
Attaches to operating hook for simple winding action to open and close.

ZOZ 032 short control rod
(60cm long).

Within reach situations


ZZZ 212 winder handle

Replaces operating hook for simple winding action to open and close.

Important considerations

- VELUX VCM Skylights can be used for flat and low sloping roofs. The low profile external covering and glazing seal prevents water infiltration even at 0°. To help prevent water 'ponding' on the glass a slight pitch (e.g. 3°-5°) is recommended.
- VELUX VCM does not come with a flashing kit but can be used with a variety of custom-made curb flashings. Contact VELUX or a local flashing manufacturer for more information.

Preparation guide for custom-made flashing



Throat on custom-made flashing must not exceed 35mm – otherwise Gyprock, when installed, will encroach upon glass area.

[‡]Skylight must be installed with timber hob and Gyprock, as shown (typical installation), to achieve 2.9 U-value rating.

Opening Restrictors

BCA 2013 Vol 1&2 regulations (Prevention of Falls from Windows–Balustrades & Barriers): contact VELUX for information relating to restrictor devices for within-reach opening skylights.

VCM – frame and glazing dimensions

2004 High Performance laminated glazing as standard

| Product/size code ▶ | 2222 | 2234 | 2246 | 3030 | 3046 | 4646 |
|------------------------------------|---------|---------|----------|---------|----------|-----------|
| Throat dimensions wxh (mm) | 692x692 | 665x970 | 665x1275 | 870x870 | 870x1275 | 1275x1275 |
| Internal glass size wxh (mm) | 495x495 | 495x799 | 495x1104 | 698x698 | 698x1104 | 1104x1104 |
| Daylight area (m ²) | 0.24 | 0.39 | 0.55 | 0.49 | 0.77 | 1.22 |
| Ventilation area (m ²) | 0.30 | 0.39 | 0.48 | 0.42 | 0.54 | 0.66 |
| 2004 High Performance glazing | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Weight in kg* | 19.9 | 20.9 | 32.3 | 29.2 | 33.6 | 55.1 |

Skylights can only be installed as per orientation depicted above.

* Weight does not include flashing.

[^]Based on VELUX internal testing with 3076 model Roof Window.