Wiha SoftFinish® electric slimFix.

The convenient slim solution for electrical applications.



Applications on live equipment are subject to very special requirements. The focus is on absolute user safety and Wiha demonstrates this with a wealth of details.

The high quality blade insulation is moulded directly onto the blade and therefore guarantees safety when working on live equipment up to 1,500 V DC/ 1,000 V AC. To maintain this safety, each screwdriver of the SoftFinish® electric series is individually tested in a water bath at 10,000 Volts according to IEC 60900:2012.

The roll-off protection and the special handle geometry offer optimum handling and electrical safety, even in critical applications.



slimTECHNOLOGY: Up to 33% reduction of the bit diameter in the critical working area allows effortless access to low-lying fastening/spring





- Unlimited access
- Blades up to 33% narrower due to integrated insulation
- Tool for spring clips (wedgeprofiled output geometry)









Safety Notice:

When working with VDE tools, observe the national safety and accident prevention regulations!



For slotted, Phillips and Pozidriv screws.



SoftFinish® electric slimFix slotted screwdriver.

Individually tested protective insulation 1,000 V AC, VDE and GS

tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened,

black-finish. Protective insulation moulded directly onto the blade and completely integrated into the blade in the lower area.

Handle: Ergonomic Wiha SoftFinish® multi-component

handle with roll-off protection.

DIN ISO 2380 Standards:

Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC. Extra: The integrated protective insulation enables low-lying fastening and

spring elements to be reached and manipulated.

Order-No.	1	=	\ominus ;	===	- ÷	
35446	3.5	100	0.6	204	23	10
35390	4.0	100	0.8	211	30	10
35501	4.5	125	1.0	236	30	10
35391	5.5	125	1.0	243	36	10
35392	6.5	150	1.2	268	36	10



DYE 60900 V JEC 60900 2012

SoftFinish® electric slimFix Phillips screwdriver. 3211

Individually tested protective insulation 1,000 V AC, VDE and GS

tested.

DIN ISO 8764. Manufactured acc. to IEC 60900:2012. Blade:

Application: The integrated protective insulation enables low-lying fastening

elements to be reached and manipulated.

Order-No.	⊕	= ■	==	-	
35393	PH1	80	191	30	10
35394	PH2	100	218	36	10



© 1000 V IEC 60900:2012

SoftFinish® electric slimFix Pozidriv screwdriver. 3241

Individually tested protective insulation 1,000 V AC, VDE and GS

DIN ISO 8764. Manufactured acc. to IEC 60900:2012. Blade: The integrated protective insulation enables low-lying fastening Application:

elements to be reached and manipulated.

Order-No.	₩	=	==	- ÷	
35395	PZ1	80	191	30	10
35396	PZ2	100	218	36	10

For TORX®-, terminal- and square-drive screws.



1000 V FC 60900:2012

SoftFinish® electric slimFix TORX® screwdriver.

Individually tested protective insulation 1,000 V AC, VDE and GS

Blade: DIN ISO 8764. Manufactured acc. to IEC 60900:2012.

Application: The integrated protective insulation enables low-lying fastening and

spring elements to be reached and manipulated.

Smaller sizes from T9 contained in the 325 series.

Order-No.		 ■		-	
36536	T10	100	204	23	10
36537	T15	100	211	30	10
36538	T20	100	211	30	10
36539	T25	125	243	36	10
36540	T27	125	243	36	10
36541	T30	125	243	36	10
36542	T40	150	268	36	5





SoftFinish® electric slimFix Xeno screwdriver.

For terminal screws (slotted/ Phillips).

Individually tested protective insulation 1,000 V AC, VDE and GS tested.

36

Blade: Manufactured acc. to IEC 60900:2012. Order-No. **(** 35502 SL/PH1 80 191 30 10 SL/PH2 35503 100 10 218



1000 V IEC 60900:2012

SoftFinish® electric slimFix Xeno screwdriver.

For terminal screws (slotted/ Pozidriv).

Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Blade Manufactured acc. to IEC 60900:2012.

Order-No.	₩	 →	==	- ÷	
36329	SL/PZ1	80	191	30	10
36330	SL/PZ2	100	218	36	10



©EC 60900:2012

3581 SoftFinish® electric slimFix square (Robertson) screwdrivers. Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Blade: Manufactured acc. to IEC 60900:2012.

Order-No.			=	==	— <u></u>		
35504	Robertson 1	2.3	100	211	30	10	
35505	Robertson 2	28	125	243	36	10	

Wiha SoftFinish® electric slimFix.

The convenient slim solution for electrical applications.

SoftFinish® electric slimFix sets.



SoftFinish® electric slimFix slotted/ Phillips screwdriver set, 2-pcs. Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Blister packed.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened,

Protective insulation moulded directly onto the blade and completely

integrated into the blade in the lower area.

Ergonomic Wiha SoftFinish® multi-component handle with roll-off pro-Handle:

Manufactured acc. to IEC 60900:2012. Standards:

Application: For all work on or around electrical components up to 1,000 V AC.

Extra: The integrated protective insulation enables low-lying fastening and

spring elements to be reached and manipulated.

Order-No.	Series		
36331	SB 320	1 S201	1
Φ	3201	3.5x100	
(1)	3211	PH2x100	



SoftFinish® electric slimFix slotted/ Pozidriv screwdriver set, 2-pcs. Individually tested protective insulation 1,000 V AC, VDE and GS

Blister packed.

tested.

Order-No.	Series			
36332	SB 320	SB 3201 S202		1
Φ	3201	3.5x100		
₩.	3241	P72x100		



SoftFinish® electric slimFix slotted/ Xeno screwdriver set, 2-pcs.

For terminal screws (slotted/ Pozidriv).

Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Blister packed.

Order-No.	Series		
36333	SB 3201	S204	1
Φ	3201	3.5x100	
₩	3281	SL/PZ2x100	

SoftFinish® electric slimFix sets.



3201 K6

SoftFinish® electric slimFix slotted/ Phillips screwdriver set, 6 pcs. Individually tested protective insulation 1,000 V AC, VDE and GS

Blade: High quality chrome-vanadium-molybdenum steel, through hardened,

black-finish.

Protective insulation moulded directly onto the blade and completely

integrated into the blade in the lower area.

Ergonomic Wiha SoftFinish® multi-component handle with roll-off pro-Handle:

Manufactured acc. to IEC 60900:2012. Standards:

Application: For all work on or around electrical components up to 1,000 V AC. The integrated protective insulation enables low-lying fastening and Extra:

spring elements to be reached and manipulated.

Order-No.	Series				
35389	3201 K6				1
Φ	3201	3.5x100	4.0x100	5.5x125	6.5x150
(1)	3211	PH1x80	PH2x100		



SoftFinish® electric slimFix slotted/ Pozidriv screwdriver set, 6-pcs. Individually tested protective insulation 1,000 V AC, VDE and GS

Blade: Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC. Extra: The integrated protective insulation enables low-lying fastening and

spring elements to be reached and manipulated.

Order-No.	Series				
36455	3201 ZK6	6			1
(3201	3.5x100	4.0x100	5.5x125	6.5x150
⊕	3241	PZ1x80	PZ2x100		



SoftFinish® electric slimFix sets.



NEW

Extra:

© 1000 V IEC 60900:2012

3201 K6 01 SoftFinish® electric slimFix slotted/Phillips/Pozidriv Xeno screwdri-

ver set, 6-pcs.

Individually tested protective insulation 1,000 V AC, VDE and GS

tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened,

black-finish.

Protective insulation moulded directly onto the blade and completely

integrated into the blade in the lower area.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off pro-

tection.

Standards: Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

The integrated protective insulation enables low-lying fastening and

spring elements to be reached and manipulated.

Order-No.	Series					
38362	3201 K6 0	1			1	
1	3201	3.5x100	4.0x100	5.5x125		
⊕	3211	PH1x80	PH2x100			
(♣)	3281	SL/PZ2 x 100				





\bigcirc 1000 V $_{\rm IEC}$ 60900:2012

3251 K6 SoftFinish® electric slimFix TORX® screwdriver set, 6-pcs.

Individually tested protective insulation 1,000 V AC, VDE and GS $\,$

tested.

Blade: Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

Extra: The integrated protective insulation enables low-lying fastening

elements to be reached and manipulated.

Order-No.	Series				
36558	3251 K6				1
	325	T8x60	T9x60		
	3251	T10x100	T15x100	T20x100	T25x125

Displays.





1000 V EC 60900:2012

3211 VB Display SoftFinish® electric slimFix.

Card display with 18 pcs.

Size: 28 x 13 x 36 cm (WxDxH).

Order-No.	Series			_	=
35559	3211 VB				1
1	3201	3x3.5	3x4.0	3x5.5	3x6.5
⊕	3211	3xPH1	3xPH2		



3241 VB





Display SoftFinish® electric slimFix. Card display with 18 pcs.

