

EnduraSeal

EnduraSeal Premium Grey Thread Tape

Brand Name: EnduraSeal Premium Grey Thread Tape

Product Description: P.T.F.E. Thread Seal Tape

Model Number(s): 4920482

Serial Number(s): 6958959327034

Applicable Standard(s): AS 4623-2008

Classification: Class III

Rated Working Pressure: 2000 kPa

Working Temperature Range: -20°C to +260°C

Melting Point: 330°C

Thickness: 0.10mm (+/- 0.015mm)

Length: 8m (+/- 0.5m)

Width: 12mm (+/- 0.5mm)

Density: 1.00g/cm³

Recommended Application: Suitable for use in metallic threaded joints and fittings used in Natural Gas and Liquid Petroleum Gas (LPG) installations.

Application Instructions:

1. Ensure threads are clean and free from oil and dust.
2. Apply the tape to the thread in the opposite direction of the thread. For example, tape should be applied in an anti-clockwise direction on a thread that screws clockwise.
3. For tapered threads, apply a minimum of 4 wraps to the thread. For damaged or non-tapered threads more than 4 wraps may be required.

Product Composition: 99.9% P.T.F.E. Resin.

THIS PRODUCT DOES NOT CONTAIN ASBESTOS.

Hazards Identification: Not Classified as Hazardous Goods when used and stored in the correct manner.

When subjected to fire, this product will emit fumes that could be hazardous to health, breathing apparatus and eye protection should be worn in the event of fire involving this product.

Storage: Store product in a cool dry place, discard unused product 5 years after purchase date.

First Aid Measures: Inhalation: Unlikely during proper use of product. Keep at rest and seek medical attention if symptoms develop/persist.

Ingestion: Unlikely during proper use of product. Wash out mouth with water, do not induce vomiting. seek medical attention if symptoms develop/persist.

Skin: Wash affected area with soap and water. If irritation develops seek medical attention.

Eye Contact: Unlikely during proper use of product. Flush eyes with running water until all contaminants have been removed. Seek medical attention if symptoms develop/persist.

