

JOHNSTONE'S PROFESSIONAL TIMBER STRIPPER is a fast acting, water-soluble gel timber finish and paint remover, suitable for interior and exterior application. It quickly and effectively removes most water and oil-based timber coatings including acrylics, polyurethanes and varnishes, removing multiple layers in a single application. This formulation has been specifically developed for safer and more comfortable interior usage, with no Methylene Chloride (MC) and N-Methylpyrrolidone (NMP).

ENVIRONMENTALLY RESPONSIBLE

Johnstone's Professional Timber Stripper is free from Methylene Chloride and N-Methylpyrrolidone (found in most traditional paint and varnish strippers), making it safer for interior use.

APPLICATION

IMPORTANT: USE IN A WELL VENTILATED AREA. AVOID SKIN AND EYE CONTACT.

1. Apply a thick coat by synthetic bristle brush. Do not exceed coverage rates. Take care on vertical or overhanging surfaces as Johnstone's Professional Timber Stripper may drip.
2. Allow 15 – 20 minutes to penetrate and soften or wrinkle the coating. Stripping times will vary depending on the type of finish, thickness of the coating to be removed and age of the coating.
3. Test with a paint scraper to ensure that the coating is easily removed.
4. Remove using a paint scraper or if appropriate, a high pressure water cleaner. On timber surfaces, work in the direction of the grain. On curved, rough surfaces or mouldings, use a synthetic hard bristle brush or scourer.
5. **IMPORTANT:** The stripper remains active while in a wet state. Do not allow Johnstone's Professional Timber Stripper to dry on the surface. For best results, cover with a plastic drop sheet to stop Johnstone's Professional Timber Stripper from drying out and work in small areas at a time.
6. **NOTE:** Some oil based coatings will continue to bubble and strip even after the stripper has been removed.
7. Thick or stubborn coatings may require more than one application.
8. Clean stripped surfaces thoroughly with water and allow to dry.
9. Sand as necessary to remove any residue before refinishing the surface.

CLEAN UP: Clean brushes and equipment with water.

Further information:

AUS: www.johnstoneswoodcare.com.au

NZ: www.johnstoneswoodcare.co.nz

IDEAL FOR: → The removal of most water and oil based timber coatings including acrylics, polyurethanes and varnishes.

SUITABLE SURFACES: → Most exterior and interior timber surfaces. Note: Not suitable for epoxies and 2-Pack oil based coatings. Do not use on plastic surfaces, vinyl, masonite or rubber.

COVERAGE: → Approximately 0.5 square metres per litre when applied 2mm thick on a horizontal surface.

SAFETY & FIRST AID

WARNING FLAMMABLE LIQUID AND VAPOUR.

KEEP OUT OF REACH OF CHILDREN. READ THE LABEL BEFORE USE. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Keep cool. Dispose of contents and container in accordance with all local, regional, national and international regulations. Do not pour leftover product down drains.

SAFETY & FIRST AID

- Wear protective gloves.
- Wear eye or face protection.
- Wear protective clothing.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Immediately call a POISON CENTRE or physician.
- IF IN EYES: Rinse with plenty of running water for 15 minutes. Seek medical advice if irritation occurs.
- If medical advice is needed, have product container or label at hand.

CONTAINS

(2-methoxymethylethoxy)propanol 30 - <60%,
benzyl alcohol 1 - <10%,
ethyl 3-ethoxypropionate 1 - <10%.

FOR 24 HOUR MEDICAL EMERGENCY RESPONSE SERVICE CALL:

AUSTRALIA:
1800 883 254

NEW ZEALAND:
0800 000 096

